


ACCESSIBILITY

Compact design ideal for restricted access

DURABILITY

Proven to be one of the most robust products in the market, the first choice for arduous conditions

ACCURACY

Exceeds requirements of ISO 6789

SCALE

Multiple scales - Nm, kg.m, lbf.in and lbf.ft are branded into steel tube, giving reliability for the life of the product

FLEXIBILITY

Push-through square drive for left and right hand operation

SETTING

Retractable adjuster knob cannot be altered by accident

SERVICE

Fully repairable with dedicated service kits

- Certified accuracy to $\pm 4\%$

AVT100A

3/8" Classic

Part No.	Square Drive	Torque range Nm	Length mm	Box Qty	M.R.P
AVT100A	3/8	2.5-11	318	1	9,654
AVT300A	3/8	5-33	422	1	9,806
AVT600	3/8	12-68	476	1	10,268

EVT600A

EVT3000A

1 1/2" Classic

Part No.	Square Drive	Torque range Nm	Length mm	Box Qty	M.R.P
EVT600A	1 1/2	12-68	476	1	10,268
EVT1200A	1 1/2	25-135	546	1	10,904
EVT2000A	1 1/2	50-225	597	1	11,375
EVT3000A	1 1/2	70-330	825	1	12,924


Torque Measurement Conversion Chart

TO CONVERT FROM	TO CONVERT TO								
	mN.m	cN.m	N.m	daN.m	cm.kg	m.kg	in.oz	in.lb	ft.lb
millinewton metre	centinewton metre	newton metre	decanewton metre	centimetre kg	metre kg	inch-ounce	inch-pound	foot-pound	
1mN.m	1	0.1	0.001	0.0001	0.0102	0.000102	0.1418	0.00886	0.000738
1cN.m	10	1	0.01	0.001	0.102	0.00102	1.418	0.0886	0.00738
1N.m	1000	100	1	0.1	10.2	0.102	141.8	8.863	0.738
1daN.m	10000	1000	10	1	10.2	1.02	1418	88.63	7.38
1cm.kg	98	9.8	0.098	0.0098	1	0.01	13.9	0.869	0.0724
1m.kg	9810	981	9.81	0.98	100	1	1390	86.90	7.24
1in.oz	7.05	0.705	0.00705	0.0007	0.072	0.0072	1	0.063	0.0052
1in.lb	112.8	11.28	0.1128	0.01128	1.152	1.0115	16	1	0.083
1ft.lb	1350	135	1.35	0.135	13.8	0.138	192	12	1

Convert 10 ft.lb to N.m, 10ft.lb x 1.35 = 13.5 N.m

HVT5000

GVT8400

3/4" & 1" Classic

Part No.	Square Drive	Torque range Nm	Length mm	Box Qty	M.R.P
HVT5000	3/4	140-560	1130	1	29,655
HVT7200	3/4	200-810	1181	1	30,307
GVT8400	1	480-940	1397	1	45,014

E200T


- Strong Ratchet Mechanism - 5° minimum working arc
- Window Scale, Slim head with Aluminium handle
- Positive lock - preventing accidental adjustment whilst in use

3/8" & 1/2" Ratcheting Type

Part No.	Square Drive	Torque range Nm	Length mm	Box Qty	M.R.P
A50T	3/8	10-50	335	1	7,564
E200T	1/2	40-200	510	1	8,091
E304T	1/2	60-340	625	1	9,073

- Exceeds the requirements of ISO 6789

