## **FASTENING TOOLS**

## **Features & Benefits**

 Most Stanley staplers offer our easy squeeze design which allows for less force to squeeze design which allows for less force to squeeze the handle and provides moredriving power AntiJam mechasim on most Stanley staplers

 Color coded fastener identification system on both staple gun and staple packaging makes size and

product selection a cinch





MaxSteel ™C Clamps

Soldering Iron



- · High-visibility, corrosion-resistant finish
- Advanced frame design resists flexing and bending
- · Heavy-duty, malleable iron and steel construction
- Roll-formed screw threads ensure smooth operation and durability
- · Oversized "T" handle for extra torque

Part No.	Length		Box Qty	M.R.P	
	mm	inches	Bux uty	IVI.n.F	
83-031K	25mm x 30mm	1" x 1 3/16"	30	118	
83-032K	50mm x 33mm	2" x 1 5/16"	20	146	
83-033K	75mm x 57mm	3" x 2 1/4"	12	307	
83-034K	100mm x 75mm	4" x 3"	12	443	
83-035K	150mm x 89mm	6" x 3 1/2"	8	742	



- -Suitable for soldering light gauze wires, thin metals and hobby
- ·Reaches working temperature in 12 seconds
- ·Comes with 2 soldering tips

Part No.	Contents	Pin Head	Box Qty	M.R.P
69-031B	30w/220v	Round	20	410

## Riveter





- 69-799 body is nickel plated
- · Versatile tool for joining sheet metal, fabric, leather, plastic parts, etc
- · Spring loaded handle ejects rivets stem
- All steel body with non-slip grip and wrench for changing nosepieces

Part No.	Contents	Pin Head	Box Oty	M.R.P
69-646	Medium duty riveter c/w 3 nosepieces for 1/8",5/32", 3/16" rivets	Round	5	765
69-799	Heavy duty riveter c/w 4 nosepieces for 3/32", 1/8", 5/32", 3/16" rivets	Flat	6	1,020

## GluePro™ Trigger Feed Hot Melt Glue Gun



- · Quality engineered for reliable performance
- · Trigger-feed mechanism controls glue flow
- Heats up quickly and bonds within 60 seconds
- Uses standard hot melt glue sticks
- Fold-out stand for safe, handy storage while in use

Part No.	Contents	Glue Stick	Box	M.R.
69-GR20B	Trigger Feed Hot Melt Glue Gun 100-240V/40W Round Pin	GS20DT/25DT/GS260 &500	6	619