

## Programmable DC Electronic Load

»» Product specification sheet



Kindly follow our WeChat official account for more information

# Programmable DC Electronic Load

---

## Contents

EL200VDC3400W-----	01	EL1200VDC3400W-----	29
EL200VDC4400W-----	02	EL1200VDC4400W-----	30
EL200VDC5600W-----	03	EL1200VDC5600W-----	31
EL200VDC6600W-----	04	EL1200VDC6600W-----	32
EL200VDC8800W-----	05	EL1200VDC8800W-----	33
EL200VDC11000W-----	06	EL1200VDC11000W-----	34
EL200VDC13200W-----	07	EL1200VDC13200W-----	35
EL200VDC15400W-----	08	EL1200VDC15400W-----	36
EL200VDC17600W-----	09	EL1200VDC17600W-----	37
EL200VDC19800W-----	10	EL1200VDC19800W-----	38
EL200VDC22000W-----	11	EL1200VDC22000W-----	39
EL200VDC24200W-----	12	EL1200VDC24200W-----	40
EL200VDC26400W-----	13	EL1200VDC26400W-----	41
200V Series System Specifications-----	14	1200V Series System Specifications-----	42
EL600VDC3400W-----	15		
EL600VDC4400W-----	16		
EL600VDC5600W-----	17		
EL600VDC6600W-----	18		
EL600VDC8800W-----	19		
EL600VDC11000W-----	20		
EL600VDC13200W-----	21		
EL600VDC15400W-----	22		
EL600VDC17600W-----	23		
EL600VDC19800W-----	24		
EL600VDC22000W-----	25		
EL600VDC24200W-----	26		
EL600VDC26400W-----	27		
600V Series System Specifications-----	28		

# Programmable DC Electronic Load

---

## Selection List:

Model	Voltage	Current	Power	Corresponding page
EL200VDC3400W	200V	370A	3400W	P01
EL200VDC4400W	200V	480A	4400W	P02
EL200VDC5600W	200V	610A	5600W	P03
EL200VDC6600W	200V	720A	6600W	P04
EL200VDC8800W	200V	960A	8800W	P05
EL200VDC11000W	200V	1200A	11000W	P06
EL200VDC13200W	200V	1440A	13200W	P07
EL200VDC15400W	200V	1680A	15400W	P08
EL200VDC17600W	200V	1920A	17600W	P09
EL200VDC19800W	200V	2160A	19800W	P10
EL200VDC22000W	200V	2400A	22000W	P11
EL200VDC24200W	200V	2640A	24200W	P12
EL200VDC26400W	200V	2880A	26400W	P13
EL600VDC3400W	600V	250A	3400W	P15
EL600VDC4400W	600V	320A	4400W	P16
EL600VDC5600W	600V	410A	5600W	P17
EL600VDC6600W	600V	480A	6600W	P18
EL600VDC8800W	600V	640A	8800W	P19
EL600VDC11000W	600V	800A	11000W	P20
EL600VDC13200W	600V	960A	13200W	P21
EL600VDC15400W	600V	1120A	15400W	P22
EL600VDC17600W	600V	1280A	17600W	P23
EL600VDC19800W	600V	1440A	19800W	P24
EL600VDC22000W	600V	1600A	22000W	P25
EL600VDC24200W	600V	1760A	24200W	P26
EL600VDC26400W	600V	1920A	26400W	P27
EL1200VDC3400W	1200V	130A	3400W	P29
EL1200VDC4400W	1200V	160A	4400W	P30
EL1200VDC5600W	1200V	210A	5600W	P31
EL1200VDC6600W	1200V	240A	6600W	P32
EL1200VDC8800W	1200V	320A	8800W	P33
EL1200VDC11000W	1200V	400A	11000W	P34
EL1200VDC13200W	1200V	480A	13200W	P35
EL1200VDC15400W	1200V	560A	15400W	P36
EL1200VDC17600W	1200V	640A	17600W	P37
EL1200VDC19800W	1200V	720A	19800W	P38
EL1200VDC22000W	1200V	800A	22000W	P39
EL1200VDC24200W	1200V	880A	24200W	P40
EL1200VDC26400W	1200V	960A	26400W	P41

# Programmable DC Electronic Load

MODEL		EL200VDC3400W		
Rated	Voltage	0~200V		
	Current	0~370A		
	Power	0~3400W		
	Min. Operating Voltage	0.18V@37A	0.9V@185A	1.8V@370A
<b>Static Mode</b>				
Constant Current Mode	Range	0~37A	0~185A	0~370A
	Resolution	0.5mA	2mA	5mA
	Accuracy	0.05%+0.05%F.S.		
Constant Voltage Mode	Range	0~16V	0~80V	0~200V
	Resolution	0.1mV	0.5mV	2mV
	Accuracy	0.025%+0.025%F.S.		
Constant Power Mode	Range	0~340W	0~1700W	0~3400W
	Resolution	10mW	50mW	100mW
	Accuracy	0.2%+0.2%F.S.		
Constant Resistance Mode	Range	10mΩ~100Ω(16V)	40mΩ~400Ω(80V)	1000mΩ~2000Ω(200V)
	Resolution	10mΩ(16V)	40mΩ(80V)	1000mΩ(200V)
	Accuracy	$V_{in}/R_{set}*(0.2\%)+0.2\%$ I.F.S.		
<b>Dynamic Mode</b>				
CCD/CRD	T1&T2(Pro.)	0.02ms~300s		
	T1&T2(Adv.)	0.05ms~300s		
	Resolution	1μs		
	Accuracy	1μs+100ppm		
	Slew Rate(Pro.)	0.5mA/μs~3.7A/μs	2mA/μs~12.95A/μs	5mA/μs~25.9A/μs
	Slew Rate(Adv.)	0.5mA/μs~0.37A/μs	2mA/μs~1.85A/μs	5mA/μs~3.7A/μs
	Min. Rise Time(Pro.)	10μs(Typical)		
	Min. Rise Time(Adv.)	50μs(Typical)		
	Resolution	0.5mA/μs	2mA/μs	5mA/μs
	Accuracy	5%±10us		
<b>Measurement</b>				
Voltage	Range	0~16V	0~80V	0~200V
	Resolution	0.1mV	0.5mV	2mV
	Accuracy	0.015%+0.015%F.S.		
Current	Range	0~37A	0~185A	0~370A
	Resolution	0.5mA	2mA	5mA
	Accuracy	0.04%+0.04%F.S.		
Power	Range	0~340W	0~1700W	0~3400W
	Resolution	10mW	50mW	100mW
	Accuracy	0.1%+0.1%F.S.		
Sampling Frequency	500kHz			
<b>Protection</b>				
OVP	16.32V	81.6V	204V	
OCP	37.74A	188.7A	377.4A	
OPP	346.8W	1734W	3468W	
Over Temperature	70~75°C			
Overvoltage Safety Value	110%V.F.S.			
Reverse Protection	Yes			
Alarm Tone	Yes			
<b>Mechanical</b>				
Dimensions(WxHxD)	423x132.7x610mm			
Package Dimensions(WxHxD)	665x348x918mm			
Unit Net Weight	28.5kg			
Net Weight	37.3kg			
<b>AC Input</b>				
Voltage	100~240Vac			
Frequency	50~60Hz			
Power	200VA			
Fuse	2.5A			

# Programmable DC Electronic Load

MODEL		EL200VDC4400W		
Rated	Voltage	0~200V		
	Current	0~480A		
	Power	0~4400W		
	Min. Operating Voltage	0.18V@48A	0.9V@240A	1.8V@480A
<b>Static Mode</b>				
Constant Current Mode	Range	0~48A	0~240A	0~480A
	Resolution	0.5mA	2mA	5mA
	Accuracy	0.05%+0.05%F.S.		
Constant Voltage Mode	Range	0~16V	0~80V	0~200V
	Resolution	0.1mV	0.5mV	2mV
	Accuracy	0.025%+0.025%F.S.		
Constant Power Mode	Range	0~440W	0~2200W	0~4400W
	Resolution	10mW	50mW	100mW
	Accuracy	0.2%+0.2%F.S.		
Constant Resistance Mode	Range	7.5mΩ~75Ω(16V)	30mΩ~300Ω(80V)	750mΩ~1500Ω(200V)
	Resolution	7.5mΩ(16V)	30mΩ(80V)	750mΩ(200V)
	Accuracy	Vin/Rset*(0.2%)+0.2% I.F.S.		
<b>Dynamic Mode</b>				
CCD/CRD	T1&T2(Pro.)	0.02ms~300s		
	T1&T2(Adv.)	0.05ms~300s		
	Resolution	1μs		
	Accuracy	1μs+100ppm		
	Slew Rate(Pro.)	0.5mA/μs~4.8A/μs	2mA/μs~16.8A/μs	5mA/μs~33.6A/μs
	Slew Rate(Adv.)	0.5mA/μs~0.48A/μs	2mA/μs~2.4A/μs	5mA/μs~4.8A/μs
	Min. Rise Time(Pro.)	10μs(Typical)		
	Min. Rise Time(Adv.)	50μs(Typical)		
	Resolution	0.5mA/μs	2mA/μs	5mA/μs
	Accuracy	5%±10us		
<b>Measurement</b>				
Voltage	Range	0~16V	0~80V	0~200V
	Resolution	0.1mAV	0.5mV	2mV
	Accuracy	0.015%+0.015%F.S.		
Current	Range	0~48A	0~240A	0~480A
	Resolution	0.5mA	2mA	5mA
	Accuracy	0.04%+0.04%F.S.		
Power	Range	0~440W	0~2200W	0~4400W
	Resolution	10mW	50mW	100mW
	Accuracy	0.1%+0.1%F.S.		
Sampling Frequency	500kHz			
<b>Protection</b>				
OVP	16.32V	81.6V	204V	
OCP	48.96A	244.8A	489.6A	
OPP	448.8W	2244W	4488W	
Over Temperature	70~75°C			
Overvoltage Safety Value	110%VF.S.			
Reverse Protection	Yes			
Alarm Tone	Yes			
<b>Mechanical</b>				
Dimensions(WxHxD)	423x132.7x610mm			
Package Dimensions(WxHxD)	665x348x918mm			
Unit Net Weight	32.5kg			
Net Weight	41.3kg			
<b>AC Input</b>				
Voltage	100~240Vac			
Frequency	50~60Hz			
Power	200VA			
Fuse	2.5A			

# Programmable DC Electronic Load

MODEL		EL200VDC5600W		
Rated	Voltage	0~200V		
	Current	0~610A		
	Power	0~5600W		
	Min. Operating Voltage	0.18V@61A	0.9V@305A	1.8V@610A
<b>Static Mode</b>				
Constant Current Mode	Range	0~61A	0~305A	0~610A
	Resolution	0.5mA	2mA	5mA
	Accuracy	0.05%+0.05%F.S.		
Constant Voltage Mode	Range	0~16V	0~80V	0~200V
	Resolution	0.1mV	0.5mV	2mV
	Accuracy	0.025%+0.025%F.S.		
Constant Power Mode	Range	0~560W	0~2800W	0~5600W
	Resolution	10mW	50mW	100mW
	Accuracy	0.2%+0.2%F.S.		
Constant Resistance Mode	Range	7.5mΩ~75Ω(16V)	30mΩ~300Ω(80V)	750mΩ~1500Ω(200V)
	Resolution	7.5mΩ(16V)	30mΩ(80V)	750mΩ(200V)
	Accuracy	Vin/Rset*(0.2%)+0.2% I.F.S.		
<b>Dynamic Mode</b>				
CCD/CRD	T1&T2(Pro.)	0.02ms~300s		
	T1&T2(Adv.)	0.05ms~300s		
	Resolution	1μs		
	Accuracy	1μs+100ppm		
	Slew Rate(Pro.)	0.5mA/μs~6.1A/μs	2mA/μs~21.35A/μs	5mA/μs~42.7A/μs
	Slew Rate(Adv.)	0.5mA/μs~0.61A/μs	2mA/μs~3.05A/μs	5mA/μs~6.1A/μs
	Min. Rise Time(Pro.)	10μs(Typical)		
	Min. Rise Time(Adv.)	50μs(Typical)		
	Resolution	0.5mA/μs	2mA/μs	5mA/μs
	Accuracy	5%±10us		
<b>Measurement</b>				
Voltage	Range	0~16V	0~80V	0~200V
	Resolution	0.1mV	0.5mV	2mV
	Accuracy	0.015%+0.015%F.S.		
Current	Range	0~61A	0~305A	0~610A
	Resolution	0.5mA	2mA	5mA
	Accuracy	0.04%+0.04%F.S.		
Power	Range	0~560W	0~2800W	0~5600W
	Resolution	10mW	50mW	100mW
	Accuracy	0.1%+0.1%F.S.		
Sampling Frequency	500kHz			
<b>Protection</b>				
OVP	16.32V	81.6V	204V	
OCP	62.22A	311.1A	622.2A	
OPP	571.2W	2856W	5712W	
Over Temperature	70~75°C			
Overvoltage Safety Value	110%VF.S.			
Reverse Protection	Yes			
Alarm Tone	Yes			
<b>Mechanical</b>				
Dimensions(WxHxD)	423x132.7x610mm			
Package Dimensions(WxHxD)	665x348x918mm			
Unit Net Weight	32.5kg			
Net Weight	41.3kg			
<b>AC Input</b>				
Voltage	100~240Vac			
Frequency	50~60Hz			
Power	200VA			
Fuse	2.5A			



# Programmable DC Electronic Load

MODEL		EL200VDC6600W		
Rated	Voltage	0~200V		
	Current	0~720A		
	Power	0~6600W		
	Min. Operating Voltage	0.18V@72A	0.9V@360A	1.8V@720A
<b>Static Mode</b>				
Constant Current Mode	Range	0~72A	0~360A	0~720A
	Resolution	0.5mA	2mA	5mA
	Accuracy	0.05%+0.05%F.S.		
Constant Voltage Mode	Range	0~16V	0~80V	0~200V
	Resolution	0.1mV	0.5mV	2mV
	Accuracy	0.025%+0.025%F.S.		
Constant Power Mode	Range	0~660W	0~3300W	0~6600W
	Resolution	10mW	50mW	100mW
	Accuracy	0.2%+0.2%F.S.		
Constant Resistance Mode	Range	5mΩ~50Ω(16V)	20mΩ~200Ω(80V)	500mΩ~1000Ω(200V)
	Resolution	5mΩ(16V)	20mΩ(80V)	500mΩ(200V)
	Accuracy	Vin/Rset*(0.2%)+0.2% I.F.S.		
<b>Dynamic Mode</b>				
CCD/CRD	T1&T2(Pro.)	0.02ms~300s		
	T1&T2(Adv.)	0.05ms~300s		
	Resolution	1μs		
	Accuracy	1μs+100ppm		
	Slew Rate(Pro.)	0.5mA/μs~7.2A/μs	2mA/μs~25.2A/μs	5mA/μs~50.4A/μs
	Slew Rate(Adv.)	0.5mA/μs~0.72A/μs	2mA/μs~3.6A/μs	5mA/μs~7.2A/μs
	Min. Rise Time(Pro.)	10μs(Typical)		
	Min. Rise Time(Adv.)	50μs(Typical)		
	Resolution	0.5mA/μs	2mA/μs	5mA/μs
	Accuracy	5%±10us		
<b>Measurement</b>				
Voltage	Range	0~16V	0~80V	0~200V
	Resolution	0.1mV	0.5mV	2mV
	Accuracy	0.015%+0.015%F.S.		
Current	Range	0~72A	0~360A	0~720A
	Resolution	0.5mA	2mA	5mA
	Accuracy	0.04%+0.04%F.S.		
Power	Range	0~660W	0~3300W	0~6600W
	Resolution	10mW	50mW	100mW
	Accuracy	0.1%+0.1%F.S.		
Sampling Frequency	500kHz			
<b>Protection</b>				
OVP	16.32V	81.6V	204V	
OCP	73.44A	367.2A	734.4A	
OPP	673.2W	3366W	6732W	
Over Temperature	70~75°C			
Overvoltage Safety Value	110%VF.S.			
Reverse Protection	Yes			
Alarm Tone	Yes			
<b>Mechanical</b>				
Dimensions(WxHxD)	423x177x610mm			
Package Dimensions(WxHxD)	665x392x918mm			
Unit Net Weight	37.5kg			
Net Weight	47kg			
<b>AC Input</b>				
Voltage	100~240Vac			
Frequency	50~60Hz			
Power	250VA			
Fuse	3.15A			

# Programmable DC Electronic Load

MODEL		EL200VDC8800W			
Rated	Voltage	0~200V			
	Current	0~960A			
	Power	0~8800W			
	Min. Operating Voltage	0.18V@96A	0.9V@480A	1.8V@960A	
<b>Static Mode</b>					
Constant Current Mode	Range	0~96A	0~480A	0~960A	
	Resolution	1mA	5mA	10mA	
	Accuracy	0.05%+0.05%F.S.			
Constant Voltage Mode	Range	0~16V	0~80V	0~200V	
	Resolution	0.1mV	0.5mV	2mV	
	Accuracy	0.025%+0.025%F.S.			
Constant Power Mode	Range	0~880W	0~4400W	0~8800W	
	Resolution	20mW	100mW	200mW	
	Accuracy	0.2%+0.2%F.S.			
Constant Resistance Mode	Range	4mΩ~40Ω(16V)	15mΩ~150Ω(80V)	375mΩ~750Ω(200V)	
	Resolution	4mΩ(16V)	15mΩ(80V)	375mΩ(200V)	
	Accuracy	Vin/Rset*(0.2%)+0.2% I.F.S.			
<b>Dynamic Mode</b>					
CCD/CRD	T1&T2(Pro.)	0.02ms~300s			
	T1&T2(Adv.)	0.05ms~300s			
	Resolution	1μs			
	Accuracy	1μs+100ppm			
	Slew Rate(Pro.)	0.5mA/μs~9.6A/μs	2mA/μs~28.8A/μs	5mA/μs~57.6A/μs	
	Slew Rate(Adv.)	0.5mA/μs~0.96A/μs	2mA/μs~4.8A/μs	5mA/μs~9.6A/μs	
	Min. Rise Time(Pro.)	10μs(Typical)			
	Min. Rise Time(Adv.)	50μs(Typical)			
	Resolution	1mA/μs	5mA/μs	10mA/μs	
	Accuracy	5%±10us			
<b>Measurement</b>					
Voltage	Range	0~16V	0~80V	0~200V	
	Resolution	0.1mV	0.5mV	2mV	
	Accuracy	0.015%+0.015%F.S.			
Current	Range	0~96A	0~480A	0~960A	
	Resolution	1mA	5mA	10mA	
	Accuracy	0.04%+0.04%F.S.			
Power	Range	0~880W	0~4400W	0~8800W	
	Resolution	20mW	100mW	200mW	
	Accuracy	0.1%+0.1%F.S.			
Sampling Frequency	500kHz				
<b>Protection</b>					
OVP	16.32V		81.6V	204V	
OCP	97.92A		489.6A	979.2A	
OPP	897.6W		4488W	8976W	
Over Temperature	70~75°C				
Overvoltage Safety Value	110%VF.S.				
Reverse Protection	Yes				
Alarm Tone	Yes				
<b>Mechanical</b>					
Dimensions(WxHxD)	423x310x670mm				
Package Dimensions(WxHxD)	/				
Unit Net Weight	72.5kg				
Net Weight	/				
<b>AC Input</b>					
Voltage	100~240Vac				
Frequency	50~60Hz				
Power	450VA				
Fuse	5A				



# Programmable DC Electronic Load

MODEL		EL200VDC11000W		
Rated	Voltage	0~200V		
	Current	0~1200A		
	Power	0~11000W		
	Min. Operating Voltage	0.18V@120A	0.9V@600A	1.8V@1200A
<b>Static Mode</b>				
Constant Current Mode	Range	0~120A	0~600A	0~1200A
	Resolution	1mA	5mA	10mA
	Accuracy	0.05%+0.05%F.S.		
Constant Voltage Mode	Range	0~16V	0~80V	0~200V
	Resolution	0.1mV	0.5mV	2mV
	Accuracy	0.025%+0.025%F.S.		
Constant Power Mode	Range	0~1100W	0~5500W	0~11000W
	Resolution	20mW	100mW	200mW
	Accuracy	0.2%+0.2%F.S.		
Constant Resistance Mode	Range	3mΩ~30Ω(16V)	12mΩ~120Ω(80V)	300mΩ~600Ω(200V)
	Resolution	3mΩ(16V)	12mΩ(80V)	300mΩ(200V)
	Accuracy	Vin/Rset*(0.2%)+0.2% I.F.S.		
<b>Dynamic Mode</b>				
CCD/CRD	T1&T2(Pro.)	0.02ms~300s		
	T1&T2(Adv.)	0.05ms~300s		
	Resolution	1μs		
	Accuracy	1μs+100ppm		
	Slew Rate(Pro.)	1mA/μs~12A/μs	5mA/μs~30A/μs	10mA/μs~60A/μs
	Slew Rate(Adv.)	1mA/μs~1.2A/μs	5mA/μs~6A/μs	10mA/μs~12A/μs
	Min. Rise Time(Pro.)	10μs(Typical)		
	Min. Rise Time(Adv.)	50μs(Typical)		
	Resolution	1mA/μs	5mA/μs	10mA/μs
	Accuracy	5%±10us		
<b>Measurement</b>				
Voltage	Range	0~16V	0~80V	0~200V
	Resolution	0.1mV	0.5mV	2mV
	Accuracy	0.015%+0.015%F.S.		
Current	Range	0~120A	0~600A	0~1200A
	Resolution	1mA	5mA	10mA
	Accuracy	0.04%+0.04%F.S.		
Power	Range	0~1100W	0~5500W	0~11000W
	Resolution	20mW	100mW	200mW
	Accuracy	0.1%+0.1%F.S.		
Sampling Frequency	500kHz			
<b>Protection</b>				
OVP	16.32V	81.6V	204V	
OCP	122.4A	612A	1224A	
OPP	1122W	5610W	11220W	
Over Temperature	70~75°C			
Overvoltage Safety Value	110%VF.S.			
Reverse Protection	Yes			
Alarm Tone	Yes			
<b>Mechanical</b>				
Dimensions(WxHxD)	423x310x670mm			
Package Dimensions(WxHxD)	/			
Unit Net Weight	72.5kg			
Net Weight	/			
<b>AC Input</b>				
Voltage	100~240Vac			
Frequency	50~60Hz			
Power	450VA			
Fuse	5A			

# Programmable DC Electronic Load

MODEL		EL200VDC13200W		
Rated	Voltage	0~200V		
	Current	0~1440A		
	Power	0~13200W		
	Min. Operating Voltage	0.18V@144A	0.9V@720A	1.8V@1440A
<b>Static Mode</b>				
Constant Current Mode	Range	0~144A	0~720A	0~1440A
	Resolution	1mA	5mA	8mA
	Accuracy	0.05%+0.05%F.S.		
Constant Voltage Mode	Range	0~16V	0~80V	0~200V
	Resolution	0.1mV	0.5mV	2mV
	Accuracy	0.025%+0.025%F.S.		
Constant Power Mode	Range	0~1320W	0~6600W	0~13200W
	Resolution	40mW	200mW	400mW
	Accuracy	0.2%+0.2%F.S.		
Constant Resistance Mode	Range	2.5mΩ~25Ω(16V)	10mΩ~100Ω(80V)	250mΩ~500Ω(200V)
	Resolution	2.5mΩ(16V)	10mΩ(80V)	250mΩ(200V)
	Accuracy	Vin/Rset*(0.2%)+0.2% I.F.S.		
<b>Dynamic Mode</b>				
CCD/CRD	T1&T2(Pro.)	0.02ms~300s		
	T1&T2(Adv.)	0.05ms~300s		
	Resolution	1μs		
	Accuracy	1μs+100ppm		
	Slew Rate(Pro.)	1mA/μs~14.4A/μs	5mA/μs~32.4A/μs	10mA/μs~64.8A/μs
	Slew Rate(Adv.)	1mA/μs~1.44A/μs	5mA/μs~7.2A/μs	10mA/μs~14.4A/μs
	Min. Rise Time(Pro.)	10μs(Typical)		
	Min. Rise Time(Adv.)	50μs(Typical)		
	Resolution	1mA/μs	5mA/μs	10mA/μs
	Accuracy	5%±10us		
<b>Measurement</b>				
Voltage	Range	0~16V	0~80V	0~200V
	Resolution	0.1mV	0.5mV	2mV
	Accuracy	0.015%+0.015%F.S.		
Current	Range	0~144A	0~720A	0~1440A
	Resolution	1mA	5mA	10mA
	Accuracy	0.04%+0.04%F.S.		
Power	Range	0~1320W	0~6600W	0~13200W
	Resolution	40mW	200mW	400mW
	Accuracy	0.1%+0.1%F.S.		
Sampling Frequency	500kHz			
<b>Protection</b>				
OVP	16.32V	81.6V	204V	
OCP	146.88A	734.4A	1468.8A	
OPP	1346.4W	6732W	13464W	
Over Temperature	70-75°C			
Overvoltage Safety Value	110%VF.S.			
Reverse Protection	Yes			
Alarm Tone	Yes			
<b>Mechanical</b>				
Dimensions(WxHxD)	423x310x670mm			
Package Dimensions(WxHxD)	/			
Unit Net Weight	72.5kg			
Net Weight	/			
<b>AC Input</b>				
Voltage	100~240Vac			
Frequency	50~60Hz			
Power	450VA			
Fuse	5A			

# Programmable DC Electronic Load

MODEL		EL200VDC15400W		
Rated	Voltage	0~200V		
	Current	0~1680A		
	Power	0~15400W		
	Min. Operating Voltage	0.18V@168A	0.9V@840A	1.8V@1680A
<b>Static Mode</b>				
Constant Current Mode	Range	0~168A	0~840A	0~1680A
	Resolution	2mA	10mA	20mA
	Accuracy	0.05%+0.05%F.S.		
Constant Voltage Mode	Range	0~16V	0~80V	0~200V
	Resolution	0.1mV	0.5mV	2mV
	Accuracy	0.025%+0.025%F.S.		
Constant Power Mode	Range	0~1540W	0~7700W	0~15400W
	Resolution	40mW	200mW	400mW
	Accuracy	0.2%+0.2%F.S.		
Constant Resistance Mode	Range	2.5mΩ~25Ω(16V)	10mΩ~100Ω(80V)	250mΩ~500Ω(200V)
	Resolution	2.5mΩ(16V)	10mΩ(80V)	250mΩ(200V)
	Accuracy	Vin/Rset*(0.2%)+0.2% I.F.S.		
<b>Dynamic Mode</b>				
CCD/CRD	T1&T2(Pro.)	0.02ms~300s		
	T1&T2(Adv.)	0.05ms~300s		
	Resolution	1μs		
	Accuracy	1μs+100ppm		
	Slew Rate(Pro.)	2mA/μs~16.8A/μs	10mA/μs~33.6A/μs	20mA/μs~67.2A/μs
	Slew Rate(Adv.)	2mA/μs~1.68A/μs	10mA/μs~8.4A/μs	20mA/μs~16.8A/μs
	Min. Rise Time(Pro.)	10μs(Typical)		
	Min. Rise Time(Adv.)	50μs(Typical)		
	Resolution	2mA/μs	10mA/μs	20mA/μs
	Accuracy	5%±10us		
<b>Measurement</b>				
Voltage	Range	0~16V	0~80V	0~200V
	Resolution	0.1mV	0.5mV	2mV
	Accuracy	0.015%+0.015%F.S.		
Current	Range	0~168A	0~840A	0~1680A
	Resolution	2mA	10mA	20mA
	Accuracy	0.04%+0.04%F.S.		
Power	Range	0~1540W	0~7700W	0~15400W
	Resolution	40mW	200mW	400mW
	Accuracy	0.1%+0.1%F.S.		
Sampling Frequency	500kHz			
<b>Protection</b>				
OVP	16.32V	81.6V	204V	
OCP	171.36A	856.8A	1713.6A	
OPP	1570.8W	7854W	15708W	
Over Temperature	70~75°C			
Overvoltage Safety Value	110%VF.S.			
Reverse Protection	Yes			
Alarm Tone	Yes			
<b>Mechanical</b>				
Dimensions(WxHxD)	423x442x670mm			
Package Dimensions(WxHxD)	/			
Unit Net Weight	110kg			
Net Weight	/			
<b>AC Input</b>				
Voltage	100~240Vac			
Frequency	50~60Hz			
Power	700VA			
Fuse	10A			

# Programmable DC Electronic Load

MODEL		EL200VDC17600W		
Rated	Voltage	0~200V		
	Current	0~1920A		
	Power	0~17600W		
	Min. Operating Voltage	0.18V@192A	0.9V@960A	1.8V@1920A
<b>Static Mode</b>				
Constant Current Mode	Range	0~192A	0~960A	0~1920A
	Resolution	2mA	10mA	20mA
	Accuracy	0.05%+0.05%F.S.		
Constant Voltage Mode	Range	0~16V	0~80V	0~200V
	Resolution	0.1mV	0.5mV	2mV
	Accuracy	0.025%+0.025%F.S.		
Constant Power Mode	Range	0~1760W	0~8800W	0~17600W
	Resolution	100mW	500mW	1000mW
	Accuracy	0.2%+0.2%F.S.		
Constant Resistance Mode	Range	2mΩ~20Ω(16V)	7.5mΩ~75Ω(80V)	200mΩ~400Ω(200V)
	Resolution	2mΩ(16V)	7.5mΩ(80V)	200mΩ(200V)
	Accuracy	Vin/Rset*(0.2%)+0.2% I.F.S.		
<b>Dynamic Mode</b>				
CCD/CRD	T1&T2(Pro.)	0.02ms~300s		
	T1&T2(Adv.)	0.05ms~300s		
	Resolution	1μs		
	Accuracy	1μs+100ppm		
	Slew Rate(Pro.)	2mA/μs~19.2A/μs	10mA/μs~38.4A/μs	20mA/μs~76.8A/μs
	Slew Rate(Adv.)	2mA/μs~1.92A/μs	10mA/μs~9.6A/μs	20mA/μs~19.2A/μs
	Min. Rise Time(Pro.)	10μs(Typical)		
	Min. Rise Time(Adv.)	50μs(Typical)		
	Resolution	2mA/μs	10mA/μs	20mA/μs
	Accuracy	5%±10us		
<b>Measurement</b>				
Voltage	Range	0~16V	0~80V	0~200V
	Resolution	0.1mV	0.5mV	2mV
	Accuracy	0.015%+0.015%F.S.		
Current	Range	0~192A	0~960A	0~1920A
	Resolution	2mA	10mA	20mA
	Accuracy	0.04%+0.04%F.S.		
Power	Range	0~1760W	0~8800W	0~17600W
	Resolution	100mW	500mW	1000mW
	Accuracy	0.1%+0.1%F.S.		
Sampling Frequency	500kHz			
<b>Protection</b>				
OVP	16.32V	81.6V	204V	
OCP	195.84A	979.2A	1958.4A	
OPP	1795.2W	8976W	17952W	
Over Temperature	70-75°C			
Overvoltage Safety Value	110%V.F.S.			
Reverse Protection	Yes			
Alarm Tone	Yes			
<b>Mechanical</b>				
Dimensions(WxHxD)	423x442x670mm			
Package Dimensions(WxHxD)	/			
Unit Net Weight	110kg			
Net Weight	/			
<b>AC Input</b>				
Voltage	100~240Vac			
Frequency	50~60Hz			
Power	700VA			
Fuse	8A			

# Programmable DC Electronic Load

MODEL		EL200VDC19800W		
Rated	Voltage	0~200V		
	Current	0~2160A		
	Power	0~19800W		
	Min. Operating Voltage	0.18V@216A	0.9V@1080A	1.8V@2160A
<b>Static Mode</b>				
Constant Current Mode	Range	0~216A	0~1080A	0~2160A
	Resolution	2mA	10mA	20mA
	Accuracy	0.05%+0.05%F.S.		
Constant Voltage Mode	Range	0~16V	0~80V	0~200V
	Resolution	0.1mV	0.5mV	2mV
	Accuracy	0.025%+0.025%F.S.		
Constant Power Mode	Range	0~1980W	0~9900W	0~19800W
	Resolution	100mW	500mW	1000mW
	Accuracy	0.2%+0.2%F.S.		
Constant Resistance Mode	Range	1.7mΩ~16.7Ω(16V)	6.7mΩ~66.7Ω(80V)	166.7mΩ~333Ω(200V)
	Resolution	1.7mΩ(16V)	6.7mΩ(80V)	166.7mΩ(200V)
	Accuracy	Vin/Rset*(0.2%)+0.2% I.F.S.		
<b>Dynamic Mode</b>				
CCD/CRD	T1&T2(Pro.)	0.02ms~300s		
	T1&T2(Adv.)	0.05ms~300s		
	Resolution	1μs		
	Accuracy	1μs+100ppm		
	Slew Rate(Pro.)	2mA/μs~21.6A/μs	10mA/μs~43.2A/μs	20mA/μs~86.4A/μs
	Slew Rate(Adv.)	2mA/μs~2.16A/μs	10mA/μs~10.8A/μs	20mA/μs~21.6A/μs
	Min. Rise Time(Pro.)	10μs(Typical)		
	Min. Rise Time(Adv.)	50μs(Typical)		
	Resolution	2mA/μs	10mA/μs	20mA/μs
	Accuracy	5%±10us		
<b>Measurement</b>				
Voltage	Range	0~16V	0~80V	0~200V
	Resolution	0.1mV	0.5mV	2mV
	Accuracy	0.015%+0.015%F.S.		
Current	Range	0~216A	0~1080A	0~2160A
	Resolution	2mA	10mA	20mA
	Accuracy	0.04%+0.04%F.S.		
Power	Range	0~1980W	0~9900W	0~19800W
	Resolution	100mW	500mW	1000mW
	Accuracy	0.1%+0.1%F.S.		
Sampling Frequency	500kHz			
<b>Protection</b>				
OVP	16.32V	81.6V	204V	
OCP	220.32A	1101.6A	2203.2A	
OPP	2019.6W	10098W	20196W	
Over Temperature	70~75°C			
Overvoltage Safety Value	110%V.F.S.			
Reverse Protection	Yes			
Alarm Tone	Yes			
<b>Mechanical</b>				
Dimensions(WxHxD)	423x442x670mm			
Package Dimensions(WxHxD)	/			
Unit Net Weight	110kg			
Net Weight	/			
<b>AC Input</b>				
Voltage	100~240Vac			
Frequency	50~60Hz			
Power	700VA			
Fuse	8A			

# Programmable DC Electronic Load

MODEL		EL200VDC22000W		
Rated	Voltage	0~200V		
	Current	0~2400A		
	Power	0~22000W		
	Min. Operating Voltage	0.18V@240A	0.9V@1200A	1.8V@2400A
<b>Static Mode</b>				
Constant Current Mode	Range	0~240A	0~1200A	0~2400A
	Resolution	4mA	20mA	40mA
	Accuracy	0.05%+0.05%F.S.		
Constant Voltage Mode	Range	0~16V	0~80V	0~200V
	Resolution	0.1mV	0.5mV	2mV
	Accuracy	0.025%+0.025%F.S.		
Constant Power Mode	Range	0~2200W	0~11000W	0~22000W
	Resolution	100mW	500mW	1000mW
	Accuracy	0.2%+0.2%F.S.		
Constant Resistance Mode	Range	1.5mΩ~15Ω(16V)	6mΩ~60Ω(80V)	150mΩ~300Ω(200V)
	Resolution	1.5mΩ(16V)	6mΩ(80V)	150mΩ(200V)
	Accuracy	Vin/Rset*(0.2%)+0.2% I.F.S.		
<b>Dynamic Mode</b>				
CCD/CRD	T1&T2(Pro.)	0.02ms~300s		
	T1&T2(Adv.)	0.05ms~300s		
	Resolution	1μs		
	Accuracy	1μs+100ppm		
	Slew Rate(Pro.)	4mA/μs~24A/μs	20mA/μs~48A/μs	40mA/μs~96A/μs
	Slew Rate(Adv.)	4mA/μs~2.4A/μs	20mA/μs~12A/μs	40mA/μs~24A/μs
	Min. Rise Time(Pro.)	10μs(Typical)		
	Min. Rise Time(Adv.)	50μs(Typical)		
	Resolution	4mA/μs	20mA/μs	40mA/μs
	Accuracy	5%±10us		
<b>Measurement</b>				
Voltage	Range	0~16V	0~80V	0~200V
	Resolution	0.1mV	0.5mV	2mV
	Accuracy	0.015%+0.015%F.S.		
Current	Range	0~240A	0~1200A	0~2400A
	Resolution	4mA	20mA	40mA
	Accuracy	0.04%+0.04%F.S.		
Power	Range	0~2200W	0~11000W	0~22000W
	Resolution	100mW	500mW	1000mW
	Accuracy	0.1%+0.1%F.S.		
Sampling Frequency	500kHz			
<b>Protection</b>				
OVP	16.32V	81.6V	204V	
OCP	244.8A	1224A	2448A	
OPP	2244W	11220W	22440W	
Over Temperature	70-75°C			
Overvoltage Safety Value	110%V.F.S.			
Reverse Protection	Yes			
Alarm Tone	Yes			
<b>Mechanical</b>				
Dimensions(WxHxD)	423x575x670mm			
Package Dimensions(WxHxD)	/			
Unit Net Weight	145kg			
Net Weight	/			
<b>AC Input</b>				
Voltage	100~240Vac			
Frequency	50~60Hz			
Power	900VA			
Fuse	10A			



# Programmable DC Electronic Load

MODEL		EL200VDC24200W		
Rated	Voltage	0~200V		
	Current	0~2640A		
	Power	0~24200W		
	Min. Operating Voltage	0.18V@264A	0.9V@1320A	1.8V@2064A
<b>Static Mode</b>				
Constant Current Mode	Range	0~264A	0~1320A	0~2640A
	Resolution	4mA	20mA	40mA
	Accuracy	0.05%+0.05%F.S.		
Constant Voltage Mode	Range	0~16V	0~80V	0~200V
	Resolution	0.1mV	0.5mV	2mV
	Accuracy	0.025%+0.025%F.S.		
Constant Power Mode	Range	0~2420W	0~12100W	0~24200W
	Resolution	100mW	500mW	1000mW
	Accuracy	0.2%+0.2%F.S.		
Constant Resistance Mode	Range	1.5mΩ~15Ω(16V)	6mΩ~60Ω(80V)	150mΩ~300Ω(200V)
	Resolution	1.5mΩ(16V)	6mΩ(80V)	150mΩ(200V)
	Accuracy	Vin/Rset*(0.2%)+0.2% I.F.S.		
<b>Dynamic Mode</b>				
CCD/CRD	T1&T2(Pro.)	0.02ms~300s		
	T1&T2(Adv.)	0.05ms~300s		
	Resolution	1μs		
	Accuracy	1μs+100ppm		
	Slew Rate(Pro.)	4mA/μs~26.4A/μs	20mA/μs~52.8A/μs	40mA/μs~105.6A/μs
	Slew Rate(Adv.)	4mA/μs~2.64A/μs	20mA/μs~13.2A/μs	40mA/μs~26.4A/μs
	Min. Rise Time(Pro.)	10μs(Typical)		
	Min. Rise Time(Adv.)	50μs(Typical)		
	Resolution	4mA/μs	20mA/μs	40mA/μs
	Accuracy	5%±10us		
<b>Measurement</b>				
Voltage	Range	0~16V	0~80V	0~200V
	Resolution	0.1mV	0.5mV	2mV
	Accuracy	0.015%+0.015%F.S.		
Current	Range	0~264A	0~1320A	0~2640A
	Resolution	4mA	20mA	40mA
	Accuracy	0.04%+0.04%F.S.		
Power	Range	0~2420W	0~12100W	0~24200W
	Resolution	100mW	500mW	1000mW
	Accuracy	0.1%+0.1%F.S.		
Sampling Frequency	500kHz			
<b>Protection</b>				
OVP	16.32V	81.6V	204V	
OCP	269.28A	1346.4A	2692.8A	
OPP	2468.4W	12342W	24684W	
Over Temperature	70~75°C			
Overvoltage Safety Value	110%VF.S.			
Reverse Protection	Yes			
Alarm Tone	Yes			
<b>Mechanical</b>				
Dimensions(WxHxD)	423x575x670mm			
Package Dimensions(WxHxD)	/			
Unit Net Weight	145kg			
Net Weight	/			
<b>AC Input</b>				
Voltage	100~240Vac			
Frequency	50~60Hz			
Power	900VA			
Fuse	10A			

# Programmable DC Electronic Load

MODEL		EL200VDC26400W		
Rated	Voltage	0~200V		
	Current	0~2880A		
	Power	0~26400W		
	Min. Operating Voltage	0.18V@288A	0.9V@1440A	1.8V@2880A
<b>Static Mode</b>				
Constant Current Mode	Range	0~288A	0~1440A	0~2880A
	Resolution	4mA	20mA	40mA
	Accuracy	0.05%+0.05%F.S.		
Constant Voltage Mode	Range	0~16V	0~80V	0~200V
	Resolution	0.1mV	0.5mV	2mV
	Accuracy	0.025%+0.025%F.S.		
Constant Power Mode	Range	0~2640W	0~13200W	0~26400W
	Resolution	100mW	500mW	1000mW
	Accuracy	0.2%+0.2%F.S.		
Constant Resistance Mode	Range	1.3mΩ~12.5Ω(16V)	5mΩ~50Ω(80V)	125mΩ~250Ω(200V)
	Resolution	1.3mΩ(16V)	5mΩ(80V)	125mΩ(200V)
	Accuracy	Vin/Rset*(0.2%)+0.2% I.F.S.		
<b>Dynamic Mode</b>				
CCD/CRD	T1&T2(Pro.)	0.02ms~300s		
	T1&T2(Adv.)	0.05ms~300s		
	Resolution	1μs		
	Accuracy	1μs+100ppm		
	Slew Rate(Pro.)	4mA/μs~28.8A/μs	20mA/μs~57.6A/μs	40mA/μs~115.2A/μs
	Slew Rate(Adv.)	4mA/μs~2.88A/μs	20mA/μs~14.4A/μs	40mA/μs~28.8A/μs
	Min. Rise Time(Pro.)	10μs(Typical)		
	Min. Rise Time(Adv.)	50μs(Typical)		
	Resolution	4mA/μs	20mA/μs	40mA/μs
	Accuracy	5%±10us		
<b>Measurement</b>				
Voltage	Range	0~16V	0~80V	0~200V
	Resolution	0.1mV	0.5mV	2mV
	Accuracy	0.015%+0.015%F.S.		
Current	Range	0~288A	0~1440A	0~2880A
	Resolution	4mA	20mA	40mA
	Accuracy	0.04%+0.04%F.S.		
Power	Range	0~2640W	0~13200W	0~26400W
	Resolution	100mW	500mW	1000mW
	Accuracy	0.1%+0.1%F.S.		
Sampling Frequency	500kHz			
<b>Protection</b>				
OVP	16.32V	81.6V	204V	
OCP	293.76A	1468.8A	2937.6A	
OPP	2692.8W	13464W	26928W	
Over Temperature	70~75°C			
Overvoltage Safety Value	110%V.F.S.			
Reverse Protection	Yes			
Alarm Tone	Yes			
<b>Mechanical</b>				
Dimensions(WxHxD)	423x575x670mm			
Package Dimensions(WxHxD)	/			
Unit Net Weight	145kg			
Net Weight	/			
<b>AC Input</b>				
Voltage	100~240Vac			
Frequency	50~60Hz			
Power	900VA			
Fuse	10A			

200V Series System Specifications			
<b>Non Linear Mode</b>			
Range	CL	30uF~50000uF	
	RL	As CR Mode	
	Ls	0.1uH~16uH	
	Rs	30mΩ~20Ω	
Resolution	CL	1uF	
	RL	As CR Mode	
	Ls	0.1uH	
	Rs	1mΩ	
<b>Battery Discharge Mode</b>			
Battery Voltage	As CV Mode		
Current Resolution	As CC Mode		
Record	AH/WH		
Test Time	1s~100000s		
Time Resolution	1s		
<b>Program Mode</b>			
Step No.	300 Max.		
Dwell	0.1ms~4000s		
Spec Check	Voltage/Current/Power		
<b>External Waveform Control/Monitor</b>			
Control/Monitor	Voltage/Current		
Input/Output Range	0~10V		
Voltage Range	0~L_range F.S.	0~M_range F.S.	0~H_range F.S.
Current Range	0~L_range F.S.	0~M_range F.S.	0~H_range F.S.
Accuracy	0.4%F.S.		
Resolution	4mV		
Bandwidth	20kHz		
Input Impedance	10kΩ		
<b>Short Circuit</b>			
Current(CC)	Full range current value		
Voltage(CV)	Voltage value at the Max power in working mode		
Resistance(CR)	Min resistance value of CR Mode		
<b>Master/Slave</b>			
Parallel Interface	RJ45		
Parallel Quantity (Pro.)	20 units		
Parallel Quantity (Adv.)	10 units		
<b>General</b>			
Graphic Display	4.3"Color touch LCD		
Operation Key Feature	Soft key, Numeric key, Rotary Knob, Support USB disk		
Rack Mount Handles	Yes		
FAN	Temperature Control		
Interface	RS232/RS485/USB(Standard), GPIB/LAN(Optional)		
Communication Response Time	30ms		
Storage Capacity	User defined settings (300 sets), OCP settings (10 sets), OPP settings (10 sets), Default settings (1 set), Factory setting (1 set)		
<b>Environmental</b>			
Operating Temperature	0~40°C		
Storage Temperature	-20~80°C		
Temperature Coefficient	100ppm/°C(Typical)		
Relative Humidity	10~90%RH		
Altitude	≤2000m		
<b>Regulatory Compliance</b>			
Overvoltage Category	II		
Protection Degree	I		
Pollution Degree	II		
Input Impedance	800kΩ(Typical)		
Isolation Voltage	/		
Certificates	CE		

All specifications are subject to change without notice.

# Programmable DC Electronic Load

MODEL		EL600VDC3400W		
Rated	Voltage	0~600V		
	Current	0~250A		
	Power	0~3400W		
	Min. Operating Voltage	0.8V@25A	4V@125A	8V@250A
<b>Static Mode</b>				
Constant Current Mode	Range	0~25A	0~125A	0~250A
	Resolution	0.4mA	2mA	4mA
	Accuracy	0.05%+0.05%F.S.		
Constant Voltage Mode	Range	0~80V	0~150V	0~600V
	Resolution	0.5mV	1mV	5mV
	Accuracy	0.025%+0.025%F.S.		
Constant Power Mode	Range	0~340W	0~1700W	0~3400W
	Resolution	10mW	50mW	100mW
	Accuracy	0.2%+0.2%F.S.		
Constant Resistance Mode	Range	100mΩ~1000Ω(80V)	400mΩ~4000Ω(150V)	4000mΩ~8000Ω(600V)
	Resolution	100mΩ(80V)	400mΩ(150V)	4000mΩ(600V)
	Accuracy	Vin/Rset*(0.2%)+0.2% I.F.S.		
<b>Dynamic Mode</b>				
CCD/CRD	T1&T2(Pro.)	0.02ms~300s		
	T1&T2(Adv.)	0.05ms~300s		
	Resolution	1μs		
	Accuracy	1μs+100ppm		
	Slew Rate(Pro.)	0.4mA/μs~1A/μs	2mA/μs~5A/μs	4mA/μs~10A/μs
	Slew Rate(Adv.)	0.4mA/μs~0.25A/μs	2mA/μs~1.25A/μs	4mA/μs~2.5A/μs
	Min. Rise Time(Pro.)	20μs(Typical)		
	Min. Rise Time(Adv.)	50μs(Typical)		
	Resolution	0.4mA/μs	2mA/μs	4mA/μs
	Accuracy	5%±10us		
<b>Measurement</b>				
Voltage	Range	0~80V	0~150V	0~600V
	Resolution	0.5mV	1mV	5mV
	Accuracy	0.015%+0.015%F.S.		
Current	Range	0~25A	0~125A	0~250A
	Resolution	0.4mA	2mA	4mA
	Accuracy	0.04%+0.04%F.S.		
Power	Range	0~340W	0~1700W	0~3400W
	Resolution	10mW	50mW	100mW
	Accuracy	0.1%+0.1%F.S.		
Sampling Frequency	500kHz			
<b>Protection</b>				
OVP	81.6V	153V	612V	
OCP	25.5A	127.5A	255A	
OPP	346.8W	1734W	3468W	
Over Temperature	70~75°C			
Overvoltage Safety Value	110%V.F.S.			
Reverse Protection	Yes			
Alarm Tone	Yes			
<b>Mechanical</b>				
Dimensions(WxHxD)	423x132.7x610mm			
Package Dimensions(WxHxD)	665x348x918mm			
Unit Net Weight	32.5kg			
Net Weight	41.3kg			
<b>AC Input</b>				
Voltage	100~240Vac			
Frequency	50~60Hz			
Power	200VA			
Fuse	2.5A			

# Programmable DC Electronic Load

MODEL		EL600VDC4400W		
Rated	Voltage	0~600V		
	Current	0~320A		
	Power	0~4400W		
	Min. Operating Voltage	0.8V@32A	4V@160A	8V@320A
<b>Static Mode</b>				
Constant Current Mode	Range	0~32A	0~160A	0~320A
	Resolution	0.4mA	2mA	4mA
	Accuracy	0.05%+0.05%F.S.		
Constant Voltage Mode	Range	0~80V	0~150V	0~600V
	Resolution	0.5mV	1mV	5mV
	Accuracy	0.025%+0.025%F.S.		
Constant Power Mode	Range	0~440W	0~2200W	0~4400W
	Resolution	10mW	50mW	100mW
	Accuracy	0.2%+0.2%F.S.		
Constant Resistance Mode	Range	75mΩ~750Ω(80V)	300mΩ~3000Ω(150V)	3000mΩ~6000Ω(600V)
	Resolution	75mΩ(80V)	300mΩ(150V)	3000mΩ(600V)
	Accuracy	Vin/Rset*(0.2%)+0.2% I.F.S.		
<b>Dynamic Mode</b>				
CCD/CRD	T1&T2(Pro.)	0.02ms~300s		
	T1&T2(Adv.)	0.05ms~300s		
	Resolution	1μs		
	Accuracy	1μs+100ppm		
	Slew Rate(Pro.)	0.4mA/μs~1.28A/μs	2mA/μs~6.4A/μs	4mA/μs~12.8A/μs
	Slew Rate(Adv.)	0.4mA/μs~0.32A/μs	2mA/μs~1.6A/μs	4mA/μs~3.2A/μs
	Min. Rise Time(Pro.)	20μs(Typical)		
	Min. Rise Time(Adv.)	50μs(Typical)		
	Resolution	0.4mA/μs	2mA/μs	4mA/μs
	Accuracy	5%±10us		
<b>Measurement</b>				
Voltage	Range	0~80V	0~150V	0~600V
	Resolution	0.5mV	1mV	5mV
	Accuracy	0.015%+0.015%F.S.		
Current	Range	0~32A	0~160A	0~320A
	Resolution	0.4mA	2mA	4mA
	Accuracy	0.04%+0.04%F.S.		
Power	Range	0~440W	0~2200W	0~4400W
	Resolution	10mW	50mW	100mW
	Accuracy	0.1%+0.1%F.S.		
Sampling Frequency	500kHz			
<b>Protection</b>				
OVP	81.6V	153V	612V	
OCP	32.6A	163.2A	326.4A	
OPP	448.8W	2244W	4488W	
Over Temperature	70~75°C			
Overvoltage Safety Value	110%V.F.S.			
Reverse Protection	Yes			
Alarm Tone	Yes			
<b>Mechanical</b>				
Dimensions(WxHxD)	423x132.7x610mm			
Package Dimensions(WxHxD)	665x348x918mm			
Unit Net Weight	32.5kg			
Net Weight	41.3kg			
<b>AC Input</b>				
Voltage	100~240Vac			
Frequency	50~60Hz			
Power	200VA			
Fuse	2.5A			

# Programmable DC Electronic Load

MODEL		EL600VDC5600W		
Rated	Voltage	0~600V		
	Current	0~410A		
	Power	0~5600W		
	Min. Operating Voltage	0.8V@41A	4V@205A	8V@410A
<b>Static Mode</b>				
Constant Current Mode	Range	0~41A	0~205A	0~410A
	Resolution	0.4mA	2mA	4mA
	Accuracy	0.05%+0.05%F.S.		
Constant Voltage Mode	Range	0~80V	0~150V	0~600V
	Resolution	0.5mV	1mV	5mV
	Accuracy	0.025%+0.025%F.S.		
Constant Power Mode	Range	0~560W	0~2800W	0~5600W
	Resolution	10mW	50mW	100mW
	Accuracy	0.2%+0.2%F.S.		
Constant Resistance Mode	Range	60mΩ~600Ω(80V)	250mΩ~2500Ω(150V)	2500mΩ~5000Ω(600V)
	Resolution	60mΩ(80V)	250mΩ(150V)	2500mΩ(600V)
	Accuracy	Vin/Rset*(0.2%)+0.2% I.F.S.		
<b>Dynamic Mode</b>				
CCD/CRD	T1&T2(Pro.)	0.02ms~300s		
	T1&T2(Adv.)	0.05ms~300s		
	Resolution	1μs		
	Accuracy	1μs+100ppm		
	Slew Rate(Pro.)	0.4mA/μs~1.64A/μs	2mA/μs~8.2A/μs	4mA/μs~16.4A/μs
	Slew Rate(Adv.)	0.4mA/μs~0.41A/μs	2mA/μs~2.05A/μs	4mA/μs~4.1A/μs
	Min. Rise Time(Pro.)	20μs(Typical)		
	Min. Rise Time(Adv.)	50μs(Typical)		
	Resolution	0.4mA/μs	2mA/μs	4mA/μs
	Accuracy	5%±10us		
<b>Measurement</b>				
Voltage	Range	0~80V	0~150V	0~600V
	Resolution	0.5mV	1mV	5mV
	Accuracy	0.015%+0.015%F.S.		
Current	Range	0~41A	0~205A	0~410A
	Resolution	0.4mA	2mA	4mA
	Accuracy	0.04%+0.04%F.S.		
Power	Range	0~560W	0~2800W	0~5600W
	Resolution	10mW	50mW	100mW
	Accuracy	0.1%+0.1%F.S.		
Sampling Frequency	500kHz			
<b>Protection</b>				
OVP	81.6V	153V	612V	
OCP	41.82A	209.1A	418.2A	
OPP	571.2W	2856W	5712W	
Over Temperature	70~75°C			
Overvoltage Safety Value	110%V.F.S.			
Reverse Protection	Yes			
Alarm Tone	Yes			
<b>Mechanical</b>				
Dimensions(WxHxD)	423x132.7x610mm			
Package Dimensions(WxHxD)	665x348x918mm			
Unit Net Weight	32.5kg			
Net Weight	41.3kg			
<b>AC Input</b>				
Voltage	100~240Vac			
Frequency	50~60Hz			
Power	200VA			
Fuse	2.5A			



# Programmable DC Electronic Load

MODEL		EL600VDC6600W		
Rated	Voltage	0~600V		
	Current	0~480A		
	Power	0~6600W		
	Min. Operating Voltage	0.8V@48A	4V@240A	8V@480A
<b>Static Mode</b>				
Constant Current Mode	Range	0~48A	0~240A	0~480A
	Resolution	0.5mA	2mA	5mA
	Accuracy	0.05%+0.05%F.S.		
Constant Voltage Mode	Range	0~80V	0~150V	0~600V
	Resolution	0.5mV	1mV	5mV
	Accuracy	0.025%+0.025%F.S.		
Constant Power Mode	Range	0~660W	0~3300W	0~6600W
	Resolution	10mW	50mW	100mW
	Accuracy	0.2%+0.2%F.S.		
Constant Resistance Mode	Range	50mΩ~500Ω(80V)	200mΩ~2000Ω(150V)	2000mΩ~4000Ω(600V)
	Resolution	50mΩ(80V)	200mΩ(150V)	2000mΩ(600V)
	Accuracy	Vin/Rset*(0.2%)+0.2% I.F.S.		
<b>Dynamic Mode</b>				
CCD/CRD	T1&T2(Pro.)	0.02ms~300s		
	T1&T2(Adv.)	0.05ms~300s		
	Resolution	1μs		
	Accuracy	1μs+100ppm		
	Slew Rate(Pro.)	0.5mA/μs~1.92A/μs	2mA/μs~9.6A/μs	5mA/μs~19.2A/μs
	Slew Rate(Adv.)	0.5mA/μs~0.48A/μs	2mA/μs~2.4A/μs	5mA/μs~4.8A/μs
	Min. Rise Time(Pro.)	20μs(Typical)		
	Min. Rise Time(Adv.)	50μs(Typical)		
	Resolution	0.5mA/μs	2mA/μs	5mA/μs
	Accuracy	5%±10us		
<b>Measurement</b>				
Voltage	Range	0~80V	0~150V	0~600V
	Resolution	0.5mV	1mV	5mV
	Accuracy	0.015%+0.015%F.S.		
Current	Range	0~48A	0~240A	0~480A
	Resolution	0.5mA	2mA	5mA
	Accuracy	0.04%+0.04%F.S.		
Power	Range	0~660W	0~3300W	0~6600W
	Resolution	10mW	50mW	100mW
	Accuracy	0.1%+0.1%F.S.		
Sampling Frequency	500kHz			
<b>Protection</b>				
OVP	81.6V	153V	612V	
OCP	48.92A	244.8A	489.6A	
OPP	673.2W	3366W	6732W	
Over Temperature	70~75°C			
Overvoltage Safety Value	110%VF.S.			
Reverse Protection	Yes			
Alarm Tone	Yes			
<b>Mechanical</b>				
Dimensions(WxHxD)	423x177x610mm			
Package Dimensions(WxHxD)	665x392x918mm			
Unit Net Weight	37.5kg			
Net Weight	47kg			
<b>AC Input</b>				
Voltage	100~240Vac			
Frequency	50~60Hz			
Power	250VA			
Fuse	3.15A			

# Programmable DC Electronic Load

MODEL		EL600VDC8800W		
Rated	Voltage	0~600V		
	Current	0~640A		
	Power	0~8800W		
	Min. Operating Voltage	0.8V@64A	4V@320A	8V@640A
<b>Static Mode</b>				
Constant Current Mode	Range	0~64A	0~320A	0~640A
	Resolution	0.5mA	2mA	5mA
	Accuracy	0.05%+0.05%F.S.		
Constant Voltage Mode	Range	0~80V	0~150V	0~600V
	Resolution	0.5mV	1mV	5mV
	Accuracy	0.025%+0.025%F.S.		
Constant Power Mode	Range	0~880W	0~4400W	0~8800W
	Resolution	20mW	100mW	200mW
	Accuracy	0.2%+0.2%F.S.		
Constant Resistance Mode	Range	37.5mΩ~375Ω(80V)	150mΩ~1500Ω(150V)	1500mΩ~3000Ω(600V)
	Resolution	37.5mΩ(80V)	150mΩ(150V)	1500mΩ(600V)
	Accuracy	Vin/Rset*(0.2%)+0.2% I.F.S.		
<b>Dynamic Mode</b>				
CCD/CRD	T1&T2(Pro.)	0.02ms~300s		
	T1&T2(Adv.)	0.05ms~300s		
	Resolution	1μs		
	Accuracy	1μs+100ppm		
	Slew Rate(Pro.)	0.5mA/μs~2.56A/μs	2mA/μs~12.8A/μs	5mA/μs~25.6A/μs
	Slew Rate(Adv.)	0.5mA/μs~0.64A/μs	2mA/μs~3.2A/μs	5mA/μs~6.4A/μs
	Min. Rise Time(Pro.)	20μs(Typical)		
	Min. Rise Time(Adv.)	50μs(Typical)		
	Resolution	0.5mA/μs	2mA/μs	5mA/μs
	Accuracy	5%±10us		
<b>Measurement</b>				
Voltage	Range	0~80V	0~150V	0~600V
	Resolution	0.5mV	1mV	5mV
	Accuracy	0.015%+0.015%F.S.		
Current	Range	0~64A	0~320A	0~640A
	Resolution	0.5mA	2mA	5mA
	Accuracy	0.04%+0.04%F.S.		
Power	Range	0~880W	0~4400W	0~8800W
	Resolution	20mW	100mW	200mW
	Accuracy	0.1%+0.1%F.S.		
Sampling Frequency	500kHz			
<b>Protection</b>				
OVP	81.6V	153V	612V	
OCP	65.28A	326.4A	652.8A	
OPP	897.6W	4488W	8976W	
Over Temperature	70~75°C			
Overvoltage Safety Value	110%V.F.S.			
Reverse Protection	Yes			
Alarm Tone	Yes			
<b>Mechanical</b>				
Dimensions(WxHxD)	423x310x670mm			
Package Dimensions(WxHxD)	/			
Unit Net Weight	72.5kg			
Net Weight	/			
<b>AC Input</b>				
Voltage	100~240Vac			
Frequency	50~60Hz			
Power	450VA			
Fuse	5A			

# Programmable DC Electronic Load

MODEL		EL600VDC11000W		
Rated	Voltage	0~600V		
	Current	0~800A		
	Power	0~11000W		
	Min. Operating Voltage	0.8V@80A	4V@400A	8V@800A
<b>Static Mode</b>				
Constant Current Mode	Range	0~80A	0~400A	0~800A
	Resolution	1mA	5mA	10mA
	Accuracy	0.05%+0.05%F.S.		
Constant Voltage Mode	Range	0~80V	0~150V	0~600V
	Resolution	0.5mV	1mV	5mV
	Accuracy	0.025%+0.025%F.S.		
Constant Power Mode	Range	0~1100W	0~5500W	0~11000W
	Resolution	20mW	100mW	200mW
	Accuracy	0.2%+0.2%F.S.		
Constant Resistance Mode	Range	30mΩ~300Ω(80V)	120mΩ~1200Ω(150V)	1200mΩ~2400Ω(600V)
	Resolution	30mΩ(80V)	120mΩ(150V)	1200mΩ(600V)
	Accuracy	$V_{in}/R_{set}*(0.2\%)+0.2\%$ I.F.S.		
<b>Dynamic Mode</b>				
CCD/CRD	T1&T2(Pro.)	0.02ms~300s		
	T1&T2(Adv.)	0.05ms~300s		
	Resolution	1μs		
	Accuracy	1μs+100ppm		
	Slew Rate(Pro.)	1mA/μs~3.2A/μs	5mA/μs~16A/μs	10mA/μs~32A/μs
	Slew Rate(Adv.)	1mA/μs~0.8A/μs	5mA/μs~4A/μs	10mA/μs~8A/μs
	Min. Rise Time(Pro.)	20μs(Typical)		
	Min. Rise Time(Adv.)	50μs(Typical)		
	Resolution	1mA/μs	5mA/μs	10mA/μs
	Accuracy	5%±10us		
<b>Measurement</b>				
Voltage	Range	0~80V	0~150V	0~600V
	Resolution	0.5mV	1mV	5mV
	Accuracy	0.015%+0.015%F.S.		
Current	Range	0~80A	0~400A	0~800A
	Resolution	1mA	5mA	10mA
	Accuracy	0.04%+0.04%F.S.		
Power	Range	0~1100W	0~5500W	0~11000W
	Resolution	20mW	100mW	200mW
	Accuracy	0.1%+0.1%F.S.		
Sampling Frequency	500kHz			
<b>Protection</b>				
OVP	81.6V	153V	612V	
OCP	81.6A	408A	816A	
OPP	1122W	5610W	11220W	
Over Temperature	70~75°C			
Overvoltage Safety Value	110%V.F.S.			
Reverse Protection	Yes			
Alarm Tone	Yes			
<b>Mechanical</b>				
Dimensions(WxHxD)	423x310x670mm			
Package Dimensions(WxHxD)	/			
Unit Net Weight	72.5kg			
Net Weight	/			
<b>AC Input</b>				
Voltage	100~240Vac			
Frequency	50~60Hz			
Power	450VA			
Fuse	5A			

# Programmable DC Electronic Load

MODEL		EL600VDC13200W		
Rated	Voltage	0~600V		
	Current	0~960A		
	Power	0~13200W		
	Min. Operating Voltage	0.8V@96A	4V@480A	8V@960A
<b>Static Mode</b>				
Constant Current Mode	Range	0~96A	0~480A	0~960A
	Resolution	1mA	5mA	10mA
	Accuracy	0.05%+0.05%F.S.		
Constant Voltage Mode	Range	0~80V	0~150V	0~600V
	Resolution	0.5mV	1mV	5mV
	Accuracy	0.025%+0.025%F.S.		
Constant Power Mode	Range	0~1320W	0~6600W	0~13200W
	Resolution	40mW	200mW	400mW
	Accuracy	0.2%+0.2%F.S.		
Constant Resistance Mode	Range	25mΩ~250Ω(80V)	100mΩ~1000Ω(150V)	1000mΩ~2000Ω(600V)
	Resolution	25mΩ(80V)	100mΩ(150V)	1000mΩ(600V)
	Accuracy	Vin/Rset*(0.2%)+0.2%IF.S.		
<b>Dynamic Mode</b>				
CCD/CRD	T1&T2(Pro.)	0.02ms~300s		
	T1&T2(Adv.)	0.05ms~300s		
	Resolution	1μs		
	Accuracy	1μs+100ppm		
	Slew Rate(Pro.)	1mA/μs~3.84A/μs	5mA/μs~19.2A/μs	10mA/μs~38.4A/μs
	Slew Rate(Adv.)	1mA/μs~0.96A/μs	5mA/μs~4.8A/μs	10mA/μs~9.6A/μs
	Min. Rise Time(Pro.)	20μs(Typical)		
	Min. Rise Time(Adv.)	50μs(Typical)		
	Resolution	1mA/μs	5mA/μs	10mA/μs
	Accuracy	5%±10us		
<b>Measurement</b>				
Voltage	Range	0~80V	0~150V	0~600V
	Resolution	0.5mV	1mV	5mV
	Accuracy	0.015%+0.015%F.S.		
Current	Range	0~96A	0~480A	0~960A
	Resolution	1mA	5mA	10mA
	Accuracy	0.04%+0.04%F.S.		
Power	Range	0~1320W	0~6600W	0~13200W
	Resolution	40mW	200mW	400mW
	Accuracy	0.1%+0.1%F.S.		
Sampling Frequency	500kHz			
<b>Protection</b>				
OVP	81.6V	153V	612V	
OCP	97.92A	489.6A	979.2A	
OPP	1346.4W	6732W	13464W	
Over Temperature	70~75°C			
Overvoltage Safety Value	110%VF.S.			
Reverse Protection	Yes			
Alarm Tone	Yes			
<b>Mechanical</b>				
Dimensions(WxHxD)	423x310x670mm			
Package Dimensions(WxHxD)	/			
Unit Net Weight	72.5kg			
Net Weight	/			
<b>AC Input</b>				
Voltage	100~240Vac			
Frequency	50~60Hz			
Power	450VA			
Fuse	5A			

# Programmable DC Electronic Load

MODEL		EL600VDC15400W		
Rated	Voltage	0~600V		
	Current	0~1120A		
	Power	0~15400W		
	Min. Operating Voltage	0.8V@112A	4V@560A	8V@1120A
<b>Static Mode</b>				
Constant Current Mode	Range	0~112A	0~560A	0~1120A
	Resolution	1mA	5mA	10mA
	Accuracy	0.05%+0.05%F.S.		
Constant Voltage Mode	Range	0~80V	0~150V	0~600V
	Resolution	0.5mV	1mV	5mV
	Accuracy	0.025%+0.025%F.S.		
Constant Power Mode	Range	0~1540W	0~7700W	0~15400W
	Resolution	40mW	200mW	400mW
	Accuracy	0.2%+0.2%F.S.		
Constant Resistance Mode	Range	21mΩ~210Ω(80V)	85mΩ~850Ω(150V)	850mΩ~1700Ω(600V)
	Resolution	21mΩ(80V)	85mΩ(150V)	850mΩ(600V)
	Accuracy	Vin/Rset*(0.2%)+0.2% I.F.S.		
<b>Dynamic Mode</b>				
CCD/CRD	T1&T2(Pro.)	0.02ms~300s		
	T1&T2(Adv.)	0.05ms~300s		
	Resolution	1μs		
	Accuracy	1μs+100ppm		
	Slew Rate(Pro.)	1mA/μs~4.48A/μs	5mA/μs~22.4A/μs	10mA/μs~44.8A/μs
	Slew Rate(Adv.)	1mA/μs~1.12A/μs	5mA/μs~5.6A/μs	10mA/μs~11.2A/μs
	Min. Rise Time(Pro.)	20μs(Typical)		
	Min. Rise Time(Adv.)	50μs(Typical)		
	Resolution	1mA/μs	5mA/μs	10mA/μs
	Accuracy	5%±10us		
<b>Measurement</b>				
Voltage	Range	0~80V	0~150V	0~600V
	Resolution	0.5mV	1mV	5mV
	Accuracy	0.015%+0.015%F.S.		
Current	Range	0~112A	0~560A	0~1120A
	Resolution	1mA	5mA	10mA
	Accuracy	0.04%+0.04%F.S.		
Power	Range	0~1540W	0~7700W	0~15400W
	Resolution	40mW	200mW	400mW
	Accuracy	0.1%+0.1%F.S.		
Sampling Frequency	500kHz			
<b>Protection</b>				
OVP	81.6V	153V	612V	
OCP	114.24A	571.2A	1142.4A	
OPP	1570.8W	7854W	15708W	
Over Temperature	70~75°C			
Overvoltage Safety Value	110%V.F.S.			
Reverse Protection	Yes			
Alarm Tone	Yes			
<b>Mechanical</b>				
Dimensions(WxHxD)	423x442x670mm			
Package Dimensions(WxHxD)	/			
Unit Net Weight	110kg			
Net Weight	/			
<b>AC Input</b>				
Voltage	100~240Vac			
Frequency	50~60Hz			
Power	700VA			
Fuse	8A			

# Programmable DC Electronic Load

MODEL		EL600VDC17600W		
Rated	Voltage	0~600V		
	Current	0~1280A		
	Power	0~17600W		
	Min. Operating Voltage	0.8V@128A	4V@640A	8V@1280A
<b>Static Mode</b>				
Constant Current Mode	Range	0~128A	0~640A	0~1280A
	Resolution	1mA	5mA	10mA
	Accuracy	0.05%+0.05%F.S.		
Constant Voltage Mode	Range	0~80V	0~150V	0~600V
	Resolution	0.5mV	1mV	5mV
	Accuracy	0.025%+0.025%F.S.		
Constant Power Mode	Range	0~1760W	0~8800W	0~17600W
	Resolution	100mW	500mW	1000mW
	Accuracy	0.2%+0.2%F.S.		
Constant Resistance Mode	Range	18.7mΩ~187Ω(80V)	75mΩ~750Ω(150V)	750mΩ~1500Ω(600V)
	Resolution	18.7mΩ(80V)	75mΩ(150V)	750mΩ(600V)
	Accuracy	Vin/Rset*(0.2%)+0.2% I.F.S.		
<b>Dynamic Mode</b>				
CCD/CRD	T1&T2(Pro.)	0.02ms~300s		
	T1&T2(Adv.)	0.05ms~300s		
	Resolution	1μs		
	Accuracy	1μs+100ppm		
	Slew Rate(Pro.)	1mA/μs~5.12A/μs	5mA/μs~25.6A/μs	10mA/μs~51.2A/μs
	Slew Rate(Adv.)	1mA/μs~1.28A/μs	5mA/μs~6.4A/μs	10mA/μs~12.8A/μs
	Min. Rise Time(Pro.)	20μs(Typical)		
	Min. Rise Time(Adv.)	50μs(Typical)		
	Resolution	1mA/μs	5mA/μs	10mA/μs
	Accuracy	5%±10us		
<b>Measurement</b>				
Voltage	Range	0~80V	0~150V	0~600V
	Resolution	0.5mV	1mV	5mV
	Accuracy	0.015%+0.015%F.S.		
Current	Range	0~128A	0~640A	0~1280A
	Resolution	1mA	5mA	10mA
	Accuracy	0.04%+0.04%F.S.		
Power	Range	0~1760W	0~8800W	0~17600W
	Resolution	100mW	500mW	1000mW
	Accuracy	0.1%+0.1%F.S.		
Sampling Frequency	500kHz			
<b>Protection</b>				
OVP	81.6V	153V	612V	
OCP	130.56A	652.8A	1305.6A	
OPP	1795.2W	8976W	17952W	
Over Temperature	70~75°C			
Overvoltage Safety Value	110%VF.S.			
Reverse Protection	Yes			
Alarm Tone	Yes			
<b>Mechanical</b>				
Dimensions(WxHxD)	423x442x670mm			
Package Dimensions(WxHxD)	/			
Unit Net Weight	110kg			
Net Weight	/			
<b>AC Input</b>				
Voltage	100~240Vac			
Frequency	50~60Hz			
Power	700VA			
Fuse	8A			



# Programmable DC Electronic Load

MODEL		EL600VDC19800W		
Rated	Voltage	0~600V		
	Current	0~1440A		
	Power	0~19800W		
	Min. Operating Voltage	0.8V@144A	4V@720A	8V@1440A
<b>Static Mode</b>				
Constant Current Mode	Range	0~144A	0~720A	0~1440A
	Resolution	2mA	10mA	20mA
	Accuracy	0.05%+0.05%F.S.		
Constant Voltage Mode	Range	0~80V	0~150V	0~600V
	Resolution	0.5mV	1mV	5mV
	Accuracy	0.025%+0.025%F.S.		
Constant Power Mode	Range	0~1980W	0~9900W	0~19800W
	Resolution	100mW	500mW	1000mW
	Accuracy	0.2%+0.2%F.S.		
Constant Resistance Mode	Range	16.7mΩ~166.7Ω(80V)	66.7mΩ~666.7Ω(150V)	666.7mΩ~1333Ω(600V)
	Resolution	16.7mΩ(80V)	66.7mΩ(150V)	666.7mΩ(600V)
	Accuracy	Vin/Rset*(0.2%)+0.2% I.F.S.		
<b>Dynamic Mode</b>				
CCD/CRD	T1&T2(Pro.)	0.02ms~300s		
	T1&T2(Adv.)	0.05ms~300s		
	Resolution	1μs		
	Accuracy	1μs+100ppm		
	Slew Rate(Pro.)	2mA/μs~5.76A/μs	10mA/μs~28.8A/μs	20mA/μs~57.6A/μs
	Slew Rate(Adv.)	2mA/μs~1.44A/μs	10mA/μs~7.2A/μs	20mA/μs~14.4A/μs
	Min. Rise Time(Pro.)	20μs(Typical)		
	Min. Rise Time(Adv.)	50μs(Typical)		
	Resolution	2mA/μs	10mA/μs	20mA/μs
	Accuracy	5%±10us		
<b>Measurement</b>				
Voltage	Range	0~80V	0~150V	0~600V
	Resolution	0.5mV	1mV	5mV
	Accuracy	0.015%+0.015%F.S.		
Current	Range	0~144A	0~720A	0~1440A
	Resolution	2mA	10mA	20mA
	Accuracy	0.04%+0.04%F.S.		
Power	Range	0~1980W	0~9900W	0~19800W
	Resolution	100mW	500mW	1000mW
	Accuracy	0.1%+0.1%F.S.		
Sampling Frequency	500kHz			
<b>Protection</b>				
OVP	81.6V	153V	612V	
OCP	146.88A	734.4A	1468.8A	
OPP	2019.6W	10098W	20196W	
Over Temperature	70~75°C			
Overvoltage Safety Value	110%V.F.S.			
Reverse Protection	Yes			
Alarm Tone	Yes			
<b>Mechanical</b>				
Dimensions(WxHxD)	423x442x670mm			
Package Dimensions(WxHxD)	/			
Unit Net Weight	110kg			
Net Weight	/			
<b>AC Input</b>				
Voltage	100~240Vac			
Frequency	50~60Hz			
Power	700VA			
Fuse	8A			

# Programmable DC Electronic Load

MODEL		EL600VDC22000W		
Rated	Voltage	0~600V		
	Current	0~1600A		
	Power	0~22000W		
	Min. Operating Voltage	0.8V@160A	4V@800A	8V@1600A
<b>Static Mode</b>				
Constant Current Mode	Range	0~160A	0~800A	0~1600A
	Resolution	2mA	10mA	20mA
	Accuracy	0.05%+0.05%F.S.		
Constant Voltage Mode	Range	0~80V	0~150V	0~600V
	Resolution	0.5mV	1mV	5mV
	Accuracy	0.025%+0.025%F.S.		
Constant Power Mode	Range	0~2200W	0~11000W	0~22000W
	Resolution	100mW	500mW	1000mW
	Accuracy	0.2%+0.2%F.S.		
Constant Resistance Mode	Range	15mΩ~150Ω(80V)	60mΩ~600Ω(150V)	600mΩ~1200Ω(600V)
	Resolution	15mΩ(80V)	60mΩ(150V)	600mΩ(600V)
	Accuracy	Vin/Rset*(0.2%)+0.2% I.F.S.		
<b>Dynamic Mode</b>				
CCD/CRD	T1&T2(Pro.)	0.02ms~300s		
	T1&T2(Adv.)	0.05ms~300s		
	Resolution	1μs		
	Accuracy	1μs+100ppm		
	Slew Rate(Pro.)	2mA/μs~6.4A/μs	10mA/μs~32A/μs	20mA/μs~64A/μs
	Slew Rate(Adv.)	2mA/μs~1.6A/μs	10mA/μs~8A/μs	20mA/μs~16A/μs
	Min. Rise Time(Pro.)	20μs(Typical)		
	Min. Rise Time(Adv.)	50μs(Typical)		
	Resolution	2mA/μs	10mA/μs	20mA/μs
	Accuracy	5%±10us		
<b>Measurement</b>				
Voltage	Range	0~80V	0~150V	0~600V
	Resolution	0.5mV	1mV	5mV
	Accuracy	0.015%+0.015%F.S.		
Current	Range	0~160A	0~800A	0~1600A
	Resolution	2mA	10mA	20mA
	Accuracy	0.04%+0.04%F.S.		
Power	Range	0~2200W	0~11000W	0~22000W
	Resolution	100mW	500mW	1000mW
	Accuracy	0.1%+0.1%F.S.		
Sampling Frequency	500kHz			
<b>Protection</b>				
OVP	81.6V	153V	612V	
OCP	163.2A	816A	1632A	
OPP	2244W	11220W	22440W	
Over Temperature	70~75°C			
Overvoltage Safety Value	110%V.F.S.			
Reverse Protection	Yes			
Alarm Tone	Yes			
<b>Mechanical</b>				
Dimensions(WxHxD)	423x575x670mm			
Package Dimensions(WxHxD)	/			
Unit Net Weight	145kg			
Net Weight	/			
<b>AC Input</b>				
Voltage	100~240Vac			
Frequency	50~60Hz			
Power	900VA			
Fuse	10A			

# Programmable DC Electronic Load

MODEL		EL600VDC24200W		
Rated	Voltage	0~600V		
	Current	0~1760A		
	Power	0~24200W		
	Min. Operating Voltage	0.8V@176A	4V@880A	8V@1760A
<b>Static Mode</b>				
Constant Current Mode	Range	0~176A	0~880A	0~1760A
	Resolution	2mA	10mA	20mA
	Accuracy	0.05%+0.05%F.S.		
Constant Voltage Mode	Range	0~80V	0~150V	0~600V
	Resolution	0.5mV	1mV	5mV
	Accuracy	0.025%+0.025%F.S.		
Constant Power Mode	Range	0~2420W	0~12100W	0~24200W
	Resolution	100mW	500mW	1000mW
	Accuracy	0.2%+0.2%F.S.		
Constant Resistance Mode	Range	13.6mΩ~136Ω(80V)	55mΩ~550Ω(150V)	550mΩ~1100Ω(600V)
	Resolution	13.6mΩ(80V)	55mΩ(150V)	550mΩ(600V)
	Accuracy	Vin/Rset*(0.2%)+0.2% I.F.S.		
<b>Dynamic Mode</b>				
CCD/CRD	T1&T2(Pro.)	0.02ms~300s		
	T1&T2(Adv.)	0.05ms~300s		
	Resolution	1μs		
	Accuracy	1μs+100ppm		
	Slew Rate(Pro.)	2mA/μs~7.04A/μs	10mA/μs~35.2A/μs	20mA/μs~70.4A/μs
	Slew Rate(Adv.)	2mA/μs~1.76A/μs	10mA/μs~8.8A/μs	20mA/μs~17.6A/μs
	Min. Rise Time(Pro.)	20μs(Typical)		
	Min. Rise Time(Adv.)	50μs(Typical)		
	Resolution	2mA/μs	10mA/μs	20mA/μs
	Accuracy	5%±10us		
<b>Measurement</b>				
Voltage	Range	0~80V	0~150V	0~600V
	Resolution	0.5mV	1mV	5mV
	Accuracy	0.015%+0.015%F.S.		
Current	Range	0~176A	0~880A	0~1760A
	Resolution	2mA	10mA	20mA
	Accuracy	0.04%+0.04%F.S.		
Power	Range	0~2420W	0~12100W	0~24200W
	Resolution	100mW	500mW	1000mW
	Accuracy	0.1%+0.1%F.S.		
Sampling Frequency	500kHz			
<b>Protection</b>				
OVP	81.6V	153V	612V	
OCP	179.52A	897.6A	1795.2A	
OPP	2468.4W	12342W	24684W	
Over Temperature	70~75°C			
Overvoltage Safety Value	110%VF.S.			
Reverse Protection	Yes			
Alarm Tone	Yes			
<b>Mechanical</b>				
Dimensions(WxHxD)	423x575x670mm			
Package Dimensions(WxHxD)	/			
Unit Net Weight	145kg			
Net Weight	/			
<b>AC Input</b>				
Voltage	100~240Vac			
Frequency	50~60Hz			
Power	900VA			
Fuse	10A			

# Programmable DC Electronic Load

MODEL		EL600VDC26400W		
Rated	Voltage	0~600V		
	Current	0~1920A		
	Power	0~26400W		
	Min. Operating Voltage	0.8V@192A	4V@960A	8V@1920A
<b>Static Mode</b>				
Constant Current Mode	Range	0~192A	0~960A	0~1920A
	Resolution	2mA	10mA	20mA
	Accuracy	0.05%+0.05%F.S.		
Constant Voltage Mode	Range	0~80V	0~150V	0~600V
	Resolution	0.5mV	1mV	5mV
	Accuracy	0.025%+0.025%F.S.		
Constant Power Mode	Range	0~2640W	0~13200W	0~26400W
	Resolution	100mW	500mW	1000mW
	Accuracy	0.2%+0.2%F.S.		
Constant Resistance Mode	Range	12.5mΩ~125Ω(80V)	50mΩ~500Ω(150V)	500mΩ~1000Ω(600V)
	Resolution	12.5mΩ(80V)	50mΩ(150V)	500mΩ(600V)
	Accuracy	Vin/Rset*(0.2%)+0.2% I.F.S.		
<b>Dynamic Mode</b>				
CCD/CRD	T1&T2(Pro.)	0.02ms~300s		
	T1&T2(Adv.)	0.05ms~300s		
	Resolution	1μs		
	Accuracy	1μs+100ppm		
	Slew Rate(Pro.)	2mA/μs~7.68A/μs	10mA/μs~38.4A/μs	20mA/μs~76.8A/μs
	Slew Rate(Adv.)	2mA/μs~1.92A/μs	10mA/μs~9.6A/μs	20mA/μs~19.2A/μs
	Min. Rise Time(Pro.)	20μs(Typical)		
	Min. Rise Time(Adv.)	50μs(Typical)		
	Resolution	2mA/μs	10mA/μs	20mA/μs
	Accuracy	5%±10us		
<b>Measurement</b>				
Voltage	Range	0~80V	0~150V	0~600V
	Resolution	0.5mV	1mV	5mV
	Accuracy	0.015%+0.015%F.S.		
Current	Range	0~192A	0~960A	0~1920A
	Resolution	2mA	10mA	20mA
	Accuracy	0.04%+0.04%F.S.		
Power	Range	0~2640W	0~13200W	0~26400W
	Resolution	100mW	500mW	1000mW
	Accuracy	0.1%+0.1%F.S.		
Sampling Frequency	500kHz			
<b>Protection</b>				
OVP	81.6V	153V	612V	
OCP	195.84A	979.2A	1958.4A	
OPP	2692.8W	13464W	26928W	
Over Temperature	70~75°C			
Overvoltage Safety Value	110%VF.S.			
Reverse Protection	Yes			
Alarm Tone	Yes			
<b>Mechanical</b>				
Dimensions(WxHxD)	423x575x670mm			
Package Dimensions(WxHxD)	/			
Unit Net Weight	145kg			
Net Weight	/			
<b>AC Input</b>				
Voltage	100~240Vac			
Frequency	50~60Hz			
Power	900VA			
Fuse	10A			

600V Series System Specifications			
<b>Non Linear Mode</b>			
Range	CL	30uF~50000uF	
	RL	As CR Mode	
	Ls	0.1uH~16uH	
	Rs	30mΩ~20Ω	
Resolution	CL	1uF	
	RL	As CR Mode	
	Ls	0.1uH	
	Rs	1mΩ	
<b>Battery Discharge Mode</b>			
Battery Voltage	As CV Mode		
Current Resolution	As CC Mode		
Record	AH/WH		
Test Time	1s~100000s		
Time Resolution	1s		
<b>Program Mode</b>			
Step No.	300 Max.		
Dwell	0.1ms~4000s		
Spec Check	Voltage/Current/Power		
<b>External Waveform Control/Monitor</b>			
Control/Monitor	Voltage/Current		
Input/Output Range	0~10V		
Voltage Range	0~L_range F.S.	0~M_range F.S.	0~H_range F.S.
Current Range	0~L_range F.S.	0~M_range F.S.	0~H_range F.S.
Accuracy	0.4%F.S.		
Resolution	4mV		
Bandwidth	20kHz		
Input Impedance	10kΩ		
<b>Short Circuit</b>			
Current(CC)	Full range current value		
Voltage(CV)	Voltage value at the Max power in working mode		
Resistance(CR)	Min resistance value of CR Mode		
<b>Master/Slave</b>			
Parallel Interface	RJ45		
Parallel Quantity (Pro.)	20 units		
Parallel Quantity (Adv.)	10 units		
<b>General</b>			
Graphic Display	4.3"Color touch LCD		
Operation Key Feature	Soft key, Numeric key, Rotary Knob, Support USB disk		
Rack Mount Handles	Yes		
FAN	Temperature Control		
Interface	RS232/RS485/USB(Standard), GPIB/LAN(Optional)		
Communication Response Time	30ms		
Storage Capacity	User defined settings (300 sets), OCP settings (10 sets), OPP settings (10 sets), Default settings (1 set), Factory setting (1 set)		
<b>Environmental</b>			
Operating Temperature	0~40°C		
Storage Temperature	-20~80°C		
Temperature Coefficient	100ppm/°C(Typical)		
Relative Humidity	10~90%RH		
Altitude	≤2000m		
<b>Regulatory Compliance</b>			
Overvoltage Category	II		
Protection Degree	I		
Pollution Degree	II		
Input Impedance	1MΩ(Typical)		
Isolation Voltage	/		
Certificates	CE		

All specifications are subject to change without notice.

# Programmable DC Electronic Load

MODEL		EL1200VDC3400W			
Rated	Voltage	0~1200V			
	Current	0~130A			
	Power	0~3400W			
	Min. Operating Voltage	2V@13A	10V@65A	20V@130A	
<b>Static Mode</b>					
Constant Current Mode	Range	0~13A	0~65A	0~130A	
	Resolution	0.2mA	1mA	2mA	
	Accuracy	0.05%+0.05%F.S.			
Constant Voltage Mode	Range	0~150V	0~600V	0~1200V	
	Resolution	1mV	5mV	10mV	
	Accuracy	0.025%+0.025%F.S.			
Constant Power Mode	Range	0~340W	0~1700W	0~3400W	
	Resolution	10mW	50mW	100mW	
	Accuracy	0.2%+0.2%F.S.			
Constant Resistance Mode	Range	100mΩ~1000Ω(150V)	400mΩ~4000Ω(600V)	4000mΩ~8000Ω(1200V)	
	Resolution	100mΩ(150V)	400mΩ(600V)	4000mΩ(1200V)	
	Accuracy	$V_{in}/R_{set}*(0.2\%)+0.2\%$ I.F.S.			
<b>Dynamic Mode</b>					
CCD/CRD	T1&T2(Pro.)	0.02ms~300s			
	T1&T2(Adv.)	0.05ms~300s			
	Resolution	1μs			
	Accuracy	1μs+100ppm			
	Slew Rate(Pro.)	0.2mA/μs~0.65A/μs	1mA/μs~3.25A/μs	2mA/μs~6.5A/μs	
	Slew Rate(Adv.)	0.2mA/μs~0.13A/μs	1mA/μs~0.65A/μs	2mA/μs~1.3A/μs	
	Min. Rise Time(Pro.)	20μs(Typical)			
	Min. Rise Time(Adv.)	50μs(Typical)			
	Resolution	0.2mA/μs	1mA/μs	2mA/μs	
	Accuracy	5%±10us			
<b>Measurement</b>					
Voltage	Range	0~150V	0~600V	0~1200V	
	Resolution	1mV	5mV	10mV	
	Accuracy	0.015%+0.015%F.S.			
Current	Range	0~13A	0~65A	0~130A	
	Resolution	0.2mA	1mA	2mA	
	Accuracy	0.04%+0.06%F.S.			
Power	Range	0~340W	0~1700W	0~3400W	
	Resolution	10mW	50mW	100mW	
	Accuracy	0.1%+0.1%F.S.			
Sampling Frequency	500kHz				
<b>Protection</b>					
OVP	153V	612V	1224V		
OCP	13.26A	66.3A	132.6A		
OPP	346.8W	1734W	3468W		
Over Temperature	70~75°C				
Overvoltage Safety Value	110%V.F.S.				
Reverse Protection	Yes				
Alarm Tone	Yes				
<b>Mechanical</b>					
Dimensions(WxHxD)	423x132.7x610mm				
Package Dimensions(WxHxD)	665x348x918mm				
Unit Net Weight	32.5kg				
Net Weight	41.3kg				
<b>AC Input</b>					
Voltage	100~240Vac				
Frequency	50~60Hz				
Power	200VA				
Fuse	2.5A				



# Programmable DC Electronic Load

MODEL		EL1200VDC4400W		
Rated	Voltage	0~1200V		
	Current	0~160A		
	Power	0~4400W		
	Min. Operating Voltage	2V@16A	10V@80A	20V@160A
<b>Static Mode</b>				
Constant Current Mode	Range	0~16A	0~80A	0~160A
	Resolution	0.2mA	1mA	2mA
	Accuracy	0.05%+0.05%F.S.		
Constant Voltage Mode	Range	0~150V	0~600V	0~1200V
	Resolution	1mV	5mV	10mV
	Accuracy	0.025%+0.025%F.S.		
Constant Power Mode	Range	0~440W	0~2200W	0~4400W
	Resolution	10mW	50mW	100mW
	Accuracy	0.2%+0.2%F.S.		
Constant Resistance Mode	Range	75mΩ~750Ω(150V)	300mΩ~3000Ω(600V)	3000mΩ~6000Ω(1200V)
	Resolution	75mΩ(150V)	300mΩ(600V)	3000mΩ(1200V)
	Accuracy	Vin/Rset*(0.2%)+0.2% I.F.S.		
<b>Dynamic Mode</b>				
CCD/CRD	T1&T2(Pro.)	0.02ms~300s		
	T1&T2(Adv.)	0.05ms~300s		
	Resolution	1μs		
	Accuracy	1μs+100ppm		
	Slew Rate(Pro.)	0.2mA/μs~0.8A/μs	1mA/μs~4A/μs	2mA/μs~8A/μs
	Slew Rate(Adv.)	0.2mA/μs~0.16A/μs	1mA/μs~0.8A/μs	2mA/μs~1.6A/μs
	Min. Rise Time(Pro.)	20μs(Typical)		
	Min. Rise Time(Adv.)	50μs(Typical)		
	Resolution	0.2mA/μs	1mA/μs	2mA/μs
	Accuracy	5%±10us		
<b>Measurement</b>				
Voltage	Range	0~150V	0~600V	0~1200V
	Resolution	1mV	5mV	10mV
	Accuracy	0.015%+0.015%F.S.		
Current	Range	0~16A	0~80A	0~160A
	Resolution	0.2mA	1mA	2mA
	Accuracy	0.04%+0.06%F.S.		
Power	Range	0~440W	0~2200W	0~4400W
	Resolution	10mW	50mW	100mW
	Accuracy	0.1%+0.1%F.S.		
Sampling Frequency	500kHz			
<b>Protection</b>				
OVP	153V	612V	1224V	
OCP	16.32A	81.6A	163.2A	
OPP	448.8W	2244W	4488W	
Over Temperature	70~75°C			
Overvoltage Safety Value	110%V.F.S.			
Reverse Protection	Yes			
Alarm Tone	Yes			
<b>Mechanical</b>				
Dimensions(WxHxD)	423x132.7x610mm			
Package Dimensions(WxHxD)	665x348x918mm			
Unit Net Weight	32.5kg			
Net Weight	41.3kg			
<b>AC Input</b>				
Voltage	100~240Vac			
Frequency	50~60Hz			
Power	200VA			
Fuse	2.5A			

# Programmable DC Electronic Load

MODEL		EL1200VDC5600W		
Rated	Voltage	0~1200V		
	Current	0~210A		
	Power	0~5600W		
	Min. Operating Voltage	2V@21A	10V@105A	20V@210A
<b>Static Mode</b>				
Constant Current Mode	Range	0~21A	0~105A	0~210A
	Resolution	0.2mA	1mA	2mA
	Accuracy	0.05%+0.05%F.S.		
Constant Voltage Mode	Range	0~150V	0~600V	0~1200V
	Resolution	1mV	5mV	10mV
	Accuracy	0.025%+0.025%F.S.		
Constant Power Mode	Range	0~560W	0~2800W	0~5600W
	Resolution	10mW	50mW	100mW
	Accuracy	0.2%+0.2%F.S.		
Constant Resistance Mode	Range	60mΩ~600Ω(150V)	235mΩ~2300Ω(600V)	2350mΩ~4700Ω(1200V)
	Resolution	60mΩ(150V)	235mΩ(600V)	2350mΩ(1200V)
	Accuracy	$V_{in}/R_{set}*(0.2\%)+0.2\%$ I.F.S.		
<b>Dynamic Mode</b>				
CCD/CRD	T1&T2(Pro.)	0.02ms~300s		
	T1&T2(Adv.)	0.05ms~300s		
	Resolution	1μs		
	Accuracy	1μs+100ppm		
	Slew Rate(Pro.)	0.2mA/μs~1.05A/μs	1mA/μs~5.25A/μs	2mA/μs~10.5A/μs
	Slew Rate(Adv.)	0.2mA/μs~0.21A/μs	1mA/μs~1.05A/μs	2mA/μs~2.1A/μs
	Min. Rise Time(Pro.)	20μs(Typical)		
	Min. Rise Time(Adv.)	50μs(Typical)		
	Resolution	0.2mA/μs	1mA/μs	2mA/μs
	Accuracy	5%±10us		
<b>Measurement</b>				
Voltage	Range	0~150V	0~600V	0~1200V
	Resolution	1mV	5mV	10mV
	Accuracy	0.015%+0.015%F.S.		
Current	Range	0~21A	0~105A	0~210A
	Resolution	0.2mA	1mA	2mA
	Accuracy	0.04%+0.06%F.S.		
Power	Range	0~560W	0~2800W	0~5600W
	Resolution	10mW	50mW	100mW
	Accuracy	0.1%+0.1%F.S.		
Sampling Frequency	500kHz			
<b>Protection</b>				
OVP	153V	612V	1224V	
OCP	21.42A	107.1A	214.2A	
OPP	571.2W	2856W	5712W	
Over Temperature	70~75°C			
Overvoltage Safety Value	110%VF.S.			
Reverse Protection	Yes			
Alarm Tone	Yes			
<b>Mechanical</b>				
Dimensions(WxHxD)	423x132.7x610mm			
Package Dimensions(WxHxD)	665x348x918mm			
Unit Net Weight	32.5kg			
Net Weight	41.3kg			
<b>AC Input</b>				
Voltage	100~240Vac			
Frequency	50~60Hz			
Power	200VA			
Fuse	2.5A			

# Programmable DC Electronic Load

MODEL		EL1200VDC6600W			
Rated	Voltage	0~1200V			
	Current	0~240A			
	Power	0~6600W			
	Min. Operating Voltage	2V@24A	10V@120A	20V@240A	
<b>Static Mode</b>					
Constant Current Mode	Range	0~24A	0~120A	0~240A	
	Resolution	0.2mA	1mA	2mA	
	Accuracy	0.05%+0.05%F.S.			
Constant Voltage Mode	Range	0~150V	0~600V	0~1200V	
	Resolution	1mV	5mV	10mV	
	Accuracy	0.025%+0.025%F.S.			
Constant Power Mode	Range	0~660W	0~3300W	0~6600W	
	Resolution	10mW	50mW	100mW	
	Accuracy	0.2%+0.2%F.S.			
Constant Resistance Mode	Range	50mΩ~500Ω(150V)	200mΩ~2000Ω(600V)	2000mΩ~4000Ω(1200V)	
	Resolution	50mΩ(150V)	200mΩ(600V)	2000mΩ(1200V)	
	Accuracy	Vin/Rset*(0.2%)+0.2% I.F.S.			
<b>Dynamic Mode</b>					
CCD/CRD	T1&T2(Pro.)	0.02ms~300s			
	T1&T2(Adv.)	0.05ms~300s			
	Resolution	1μs			
	Accuracy	1μs+100ppm			
	Slew Rate(Pro.)	0.2mA/μs~1.2A/μs	1mA/μs~6A/μs	2mA/μs~12A/μs	
	Slew Rate(Adv.)	0.2mA/μs~0.24A/μs	1mA/μs~1.2A/μs	2mA/μs~2.4A/μs	
	Min. Rise Time(Pro.)	20μs(Typical)			
	Min. Rise Time(Adv.)	50μs(Typical)			
	Resolution	0.2mA/μs	1mA/μs	2mA/μs	
	Accuracy	5%±10us			
<b>Measurement</b>					
Voltage	Range	0~150V	0~600V	0~1200V	
	Resolution	1mV	5mV	10mV	
	Accuracy	0.015%+0.015%F.S.			
Current	Range	0~24A	0~120A	0~240A	
	Resolution	0.2mA	1mA	2mA	
	Accuracy	0.04%+0.06%F.S.			
Power	Range	0~660W	0~3300W	0~6600W	
	Resolution	10mW	50mW	100mW	
	Accuracy	0.1%+0.1%F.S.			
Sampling Frequency	500kHz				
<b>Protection</b>					
OVP	153V	612V	1224V		
OCP	24.48A	122.4A	244.8A		
OPP	673.2W	3366W	6732W		
Over Temperature	70~75°C				
Overvoltage Safety Value	110%VF.S.				
Reverse Protection	Yes				
Alarm Tone	Yes				
<b>Mechanical</b>					
Dimensions(WxHxD)	423x177x610mm				
Package Dimensions(WxHxD)	665x392x918mm				
Unit Net Weight	37.5kg				
Net Weight	47kg				
<b>AC Input</b>					
Voltage	100~240Vac				
Frequency	50~60Hz				
Power	250VA				
Fuse	3.15A				

# Programmable DC Electronic Load

MODEL		EL1200VDC8800W			
Rated	Voltage	0~1200V			
	Current	0~320A			
	Power	0~8800W			
	Min. Operating Voltage	2V@32A	10V@160A	20V@320A	
<b>Static Mode</b>					
Constant Current Mode	Range	0~32A	0~160A	0~320A	
	Resolution	0.4mA	2mA	4mA	
	Accuracy	0.05%+0.05%F.S.			
Constant Voltage Mode	Range	0~150V	0~600V	0~1200V	
	Resolution	1mV	5mV	10mV	
	Accuracy	0.025%+0.025%F.S.			
Constant Power Mode	Range	0~880W	0~4400W	0~8800W	
	Resolution	20mW	100mW	200mW	
	Accuracy	0.2%+0.2%F.S.			
Constant Resistance Mode	Range	37.5mΩ~375Ω(150V)	150mΩ~1500Ω(600V)	1500mΩ~3000Ω(1200V)	
	Resolution	37.5mΩ(150V)	150mΩ(600V)	1500mΩ(1200V)	
	Accuracy	Vin/Rset*(0.2%)+0.2% I.F.S.			
<b>Dynamic Mode</b>					
CCD/CRD	T1&T2(Pro.)	0.02ms~300s			
	T1&T2(Adv.)	0.05ms~300s			
	Resolution	1μs			
	Accuracy	1μs+100ppm			
	Slew Rate(Pro.)	0.4mA/μs~1.28A/μs	2mA/μs~6.4A/μs	4mA/μs~12.8A/μs	
	Slew Rate(Adv.)	0.4mA/μs~0.32A/μs	2mA/μs~1.6A/μs	4mA/μs~3.2A/μs	
	Min. Rise Time(Pro.)	20μs(Typical)			
	Min. Rise Time(Adv.)	50μs(Typical)			
	Resolution	0.4mA/μs	2mA/μs	4mA/μs	
	Accuracy	5%±10us			
<b>Measurement</b>					
Voltage	Range	0~150V	0~600V	0~1200V	
	Resolution	1mV	5mV	10mV	
	Accuracy	0.015%+0.015%F.S.			
Current	Range	0~32A	0~160A	0~320A	
	Resolution	0.4mA	2mA	4mA	
	Accuracy	0.04%+0.06%F.S.			
Power	Range	0~880W	0~4400W	0~8800W	
	Resolution	20mW	100mW	200mW	
	Accuracy	0.1%+0.1%F.S.			
Sampling Frequency	500kHz				
<b>Protection</b>					
OVP	153V	612V	1224V		
OCP	32.64A	163.2A	326.4A		
OPP	897.6W	4488W	8976W		
Over Temperature	70~75°C				
Overvoltage Safety Value	110%V.F.S.				
Reverse Protection	Yes				
Alarm Tone	Yes				
<b>Mechanical</b>					
Dimensions(WxHxD)	423x310x670mm				
Package Dimensions(WxHxD)	/				
Unit Net Weight	72.5kg				
Net Weight	/				
<b>AC Input</b>					
Voltage	100~240Vac				
Frequency	50~60Hz				
Power	450VA				
Fuse	5A				

# Programmable DC Electronic Load

MODEL		EL1200VDC11000W			
Rated	Voltage	0~1200V			
	Current	0~400A			
	Power	0~11000W			
	Min. Operating Voltage	2V@40A	10V@200A	20V@400A	
<b>Static Mode</b>					
Constant Current Mode	Range	0~40A	0~200A	0~400A	
	Resolution	0.4mA	2mA	4mA	
	Accuracy	0.05%+0.05%F.S.			
Constant Voltage Mode	Range	0~150V	0~600V	0~1200V	
	Resolution	1mV	5mV	10mV	
	Accuracy	0.025%+0.025%F.S.			
Constant Power Mode	Range	0~1100W	0~5500W	0~11000W	
	Resolution	20mW	100mW	200mW	
	Accuracy	0.2%+0.2%F.S.			
Constant Resistance Mode	Range	30mΩ~300Ω(150V)	120mΩ~1200Ω(600V)	1200mΩ~2400Ω(1200V)	
	Resolution	30mΩ(150V)	120mΩ(600V)	1200mΩ(1200V)	
	Accuracy	Vin/Rset*(0.2%)+0.2% I.F.S.			
<b>Dynamic Mode</b>					
CCD/CRD	T1&T2(Pro.)	0.02ms~300s			
	T1&T2(Adv.)	0.05ms~300s			
	Resolution	1μs			
	Accuracy	1μs+100ppm			
	Slew Rate(Pro.)	0.4mA/μs~1.6A/μs	2mA/μs~8A/μs	4mA/μs~16A/μs	
	Slew Rate(Adv.)	0.4mA/μs~0.4A/μs	2mA/μs~2A/μs	4mA/μs~4A/μs	
	Min. Rise Time(Pro.)	20μs(Typical)			
	Min. Rise Time(Adv.)	50μs(Typical)			
	Resolution	0.4mA/μs	2mA/μs	4mA/μs	
	Accuracy	5%±10us			
<b>Measurement</b>					
Voltage	Range	0~150V	0~600V	0~1200V	
	Resolution	1mV	5mV	10mV	
	Accuracy	0.015%+0.015%F.S.			
Current	Range	0~40A	0~200A	0~400A	
	Resolution	0.4mA	2mA	4mA	
	Accuracy	0.04%+0.06%F.S.			
Power	Range	0~1100W	0~5500W	0~11000W	
	Resolution	20mW	100mW	200mW	
	Accuracy	0.1%+0.1%F.S.			
Sampling Frequency	500kHz				
<b>Protection</b>					
OVP	153V	612V	1224V		
OCP	40.8A	204A	408A		
OPP	1122W	5610W	11220W		
Over Temperature	70-75°C				
Overvoltage Safety Value	110%V.F.S.				
Reverse Protection	Yes				
Alarm Tone	Yes				
<b>Mechanical</b>					
Dimensions(WxHxD)	423x310x670mm				
Package Dimensions(WxHxD)	/				
Unit Net Weight	72.5kg				
Net Weight	/				
<b>AC Input</b>					
Voltage	100~240Vac				
Frequency	50~60Hz				
Power	450VA				
Fuse	5A				

# Programmable DC Electronic Load

MODEL		EL1200VDC13200W			
Rated	Voltage	0~1200V			
	Current	0~480A			
	Power	0~13200W			
	Min. Operating Voltage	2V@48A	10V@240A	20V@480A	
<b>Static Mode</b>					
Constant Current Mode	Range	0~48A	0~240A	0~480A	
	Resolution	0.4mA	2mA	4mA	
	Accuracy	0.05%+0.05%F.S.			
Constant Voltage Mode	Range	0~150V	0~600V	0~1200V	
	Resolution	1mV	5mV	10mV	
	Accuracy	0.025%+0.025%F.S.			
Constant Power Mode	Range	0~1320W	0~6600W	0~13200W	
	Resolution	40mW	200mW	400mW	
	Accuracy	0.2%+0.2%F.S.			
Constant Resistance Mode	Range	25mΩ~250Ω(150V)	100mΩ~1000Ω(600V)	1000mΩ~2000Ω(1200V)	
	Resolution	25mΩ(150V)	100mΩ(600V)	1000mΩ(1200V)	
	Accuracy	Vin/Rset*(0.2%)+0.2% I.F.S.			
<b>Dynamic Mode</b>					
CCD/CRD	T1&T2(Pro.)	0.02ms~300s			
	T1&T2(Adv.)	0.05ms~300s			
	Resolution	1μs			
	Accuracy	1μs+100ppm			
	Slew Rate(Pro.)	0.4mA/μs~1.6A/μs	2mA/μs~8A/μs	4mA/μs~16A/μs	
	Slew Rate(Adv.)	0.4mA/μs~0.48A/μs	2mA/μs~2.4A/μs	4mA/μs~4.8A/μs	
	Min. Rise Time(Pro.)	20μs(Typical)			
	Min. Rise Time(Adv.)	50μs(Typical)			
	Resolution	0.4mA/μs	2mA/μs	4mA/μs	
	Accuracy	5%±10us			
<b>Measurement</b>					
Voltage	Range	0~150V	0~600V	0~1200V	
	Resolution	1mV	5mV	10mV	
	Accuracy	0.015%+0.015%F.S.			
Current	Range	0~48A	0~240A	0~480A	
	Resolution	0.4mA	2mA	4mA	
	Accuracy	0.04%+0.06%F.S.			
Power	Range	0~1320W	0~6600W	0~13200W	
	Resolution	40mW	200mW	400mW	
	Accuracy	0.1%+0.1%F.S.			
Sampling Frequency	500kHz				
<b>Protection</b>					
OVP	153V	612V	1224V		
OCP	48.96A	244.8A	489.6A		
OPP	1346.4W	6732W	13464W		
Over Temperature	70~75°C				
Overvoltage Safety Value	110%V.F.S.				
Reverse Protection	Yes				
Alarm Tone	Yes				
<b>Mechanical</b>					
Dimensions(WxHxD)	423x310x670mm				
Package Dimensions(WxHxD)	/				
Unit Net Weight	72.5kg				
Net Weight	/				
<b>AC Input</b>					
Voltage	100~240Vac				
Frequency	50~60Hz				
Power	450VA				
Fuse	5A				

# Programmable DC Electronic Load

MODEL		EL1200VDC15400W			
Rated	Voltage	0~1200V			
	Current	0~560A			
	Power	0~15400W			
	Min. Operating Voltage	2V@56A	10V@280A	20V@560A	
<b>Static Mode</b>					
Constant Current Mode	Range	0~56A	0~280A	0~560A	
	Resolution	0.5mA	2mA	5mA	
	Accuracy	0.05%+0.05%F.S.			
Constant Voltage Mode	Range	0~150V	0~600V	0~1200V	
	Resolution	1mV	5mV	10mV	
	Accuracy	0.025%+0.025%F.S.			
Constant Power Mode	Range	0~1540W	0~7700W	0~15400W	
	Resolution	40mW	200mW	400mW	
	Accuracy	0.2%+0.2%F.S.			
Constant Resistance Mode	Range	21mΩ~210Ω(150V)	85mΩ~850Ω(600V)	850mΩ~1700Ω(1200V)	
	Resolution	21mΩ(150V)	85mΩ(600V)	850mΩ(1200V)	
	Accuracy	Vin/Rset*(0.2%)+0.2% I.F.S.			
<b>Dynamic Mode</b>					
CCD/CRD	T1&T2(Pro.)	0.02ms~300s			
	T1&T2(Adv.)	0.05ms~300s			
	Resolution	1μs			
	Accuracy	1μs+100ppm			
	Slew Rate(Pro.)	0.5mA/μs~1.87A/μs	2mA/μs~9.3A/μs	5mA/μs~18.7A/μs	
	Slew Rate(Adv.)	0.5mA/μs~0.56A/μs	2mA/μs~2.8A/μs	5mA/μs~5.6A/μs	
	Min. Rise Time(Pro.)	20μs(Typical)			
	Min. Rise Time(Adv.)	50μs(Typical)			
	Resolution	0.5mA/μs	2mA/μs	5mA/μs	
	Accuracy	5%±10us			
<b>Measurement</b>					
Voltage	Range	0~150V	0~600V	0~1200V	
	Resolution	1mV	5mV	10mV	
	Accuracy	0.015%+0.015%F.S.			
Current	Range	0~56A	0~280A	0~560A	
	Resolution	0.5mA	2mA	5mA	
	Accuracy	0.04%+0.06%F.S.			
Power	Range	0~1540W	0~7700W	0~15400W	
	Resolution	40mW	200mW	400mW	
	Accuracy	0.1%+0.1%F.S.			
Sampling Frequency	500kHz				
<b>Protection</b>					
OVP	153V	612V	1224V		
OCP	57.12A	285.6A	571.2A		
OPP	1570.8W	7854W	15708W		
Over Temperature	70~75°C				
Overvoltage Safety Value	110%VF.S.				
Reverse Protection	Yes				
Alarm Tone	Yes				
<b>Mechanical</b>					
Dimensions(WxHxD)	423x442x670mm				
Package Dimensions(WxHxD)	/				
Unit Net Weight	110kg				
Net Weight	/				
<b>AC Input</b>					
Voltage	100~240Vac				
Frequency	50~60Hz				
Power	700VA				
Fuse	8A				

# Programmable DC Electronic Load

MODEL		EL1200VDC17600W			
Rated	Voltage	0~1200V			
	Current	0~640A			
	Power	0~17600W			
	Min. Operating Voltage	2V@64A	10V@320A	20V@640A	
<b>Static Mode</b>					
Constant Current Mode	Range	0~64A	0~320A	0~640A	
	Resolution	0.5mA	2mA	5mA	
	Accuracy	0.05%+0.05%F.S.			
Constant Voltage Mode	Range	0~150V	0~600V	0~1200V	
	Resolution	1mV	5mV	10mV	
	Accuracy	0.025%+0.025%F.S.			
Constant Power Mode	Range	0~1760W	0~8800W	0~17600W	
	Resolution	100mW	500mW	1000mW	
	Accuracy	0.2%+0.2%F.S.			
Constant Resistance Mode	Range	18.7mΩ~187Ω(150V)	75mΩ~750Ω(600V)	750mΩ~1500Ω(1200V)	
	Resolution	18.7mΩ(150V)	75mΩ(600V)	750mΩ(1200V)	
	Accuracy	Vin/Rset*(0.2%)+0.2% I.F.S.			
<b>Dynamic Mode</b>					
CCD/CRD	T1&T2(Pro.)	0.02ms~300s			
	T1&T2(Adv.)	0.05ms~300s			
	Resolution	1μs			
	Accuracy	1μs+100ppm			
	Slew Rate(Pro.)	0.5mA/μs~2.1A/μs	2mA/μs~10.7A/μs	5mA/μs~21.3A/μs	
	Slew Rate(Adv.)	0.5mA/μs~0.64A/μs	2mA/μs~3.2A/μs	5mA/μs~6.4A/μs	
	Min. Rise Time(Pro.)	20μs(Typical)			
	Min. Rise Time(Adv.)	50μs(Typical)			
	Resolution	0.5mA/μs	2mA/μs	5mA/μs	
	Accuracy	5%±10us			
<b>Measurement</b>					
Voltage	Range	0~150V	0~600V	0~1200V	
	Resolution	1mV	5mV	10mV	
	Accuracy	0.015%+0.015%F.S.			
Current	Range	0~64A	0~320A	0~640A	
	Resolution	0.5mA	2mA	5mA	
	Accuracy	0.04%+0.06%F.S.			
Power	Range	0~1760W	0~8800W	0~17600W	
	Resolution	100mW	500mW	1000mW	
	Accuracy	0.1%+0.1%F.S.			
Sampling Frequency	500kHz				
<b>Protection</b>					
OVP	153V	612V	1224V		
OCP	65.28A	326.4A	652.8A		
OPP	1795.2W	8976W	17952W		
Over Temperature	70~75°C				
Overvoltage Safety Value	110%V.F.S.				
Reverse Protection	Yes				
Alarm Tone	Yes				
<b>Mechanical</b>					
Dimensions(WxHxD)	423x442x670mm				
Package Dimensions(WxHxD)	/				
Unit Net Weight	110kg				
Net Weight	/				
<b>AC Input</b>					
Voltage	100~240Vac				
Frequency	50~60Hz				
Power	700VA				
Fuse	8A				



# Programmable DC Electronic Load

MODEL		EL1200VDC19800W			
Rated	Voltage	0~1200V			
	Current	0~720A			
	Power	0~19800W			
	Min. Operating Voltage	2V@72A	10V@360A	20V@720A	
<b>Static Mode</b>					
Constant Current Mode	Range	0~72A	0~360A	0~720A	
	Resolution	0.5mA	2mA	5mA	
	Accuracy	0.05%+0.05%F.S.			
Constant Voltage Mode	Range	0~150V	0~600V	0~1200V	
	Resolution	1mV	5mV	10mV	
	Accuracy	0.025%+0.025%F.S.			
Constant Power Mode	Range	0~1980W	0~9900W	0~19800W	
	Resolution	100mW	500mW	1000mW	
	Accuracy	0.2%+0.2%F.S.			
Constant Resistance Mode	Range	16.7mΩ~166.7Ω(150V)	66.7mΩ~666Ω(600V)	666.7mΩ~1333Ω(1200V)	
	Resolution	16.7mΩ(150V)	66.7mΩ(600V)	666.7mΩ(1200V)	
	Accuracy	Vin/Rset*(0.2%)+0.2% I.F.S.			
<b>Dynamic Mode</b>					
CCD/CRD	T1&T2(Pro.)	0.02ms~300s			
	T1&T2(Adv.)	0.05ms~300s			
	Resolution	1μs			
	Accuracy	1μs+100ppm			
	Slew Rate(Pro.)	0.5mA/μs~2.4A/μs	2mA/μs~12A/μs	5mA/μs~24A/μs	
	Slew Rate(Adv.)	0.5mA/μs~0.72A/μs	2mA/μs~3.6A/μs	5mA/μs~7.2A/μs	
	Min. Rise Time(Pro.)	20μs(Typical)			
	Min. Rise Time(Adv.)	50μs(Typical)			
	Resolution	0.5mA/μs	2mA/μs	5mA/μs	
	Accuracy	5%±10us			
<b>Measurement</b>					
Voltage	Range	0~150V	0~600V	0~1200V	
	Resolution	1mV	5mV	10mV	
	Accuracy	0.015%+0.015%F.S.			
Current	Range	0~72A	0~360A	0~720A	
	Resolution	0.5mA	2mA	5mA	
	Accuracy	0.04%+0.06%F.S.			
Power	Range	0~1980W	0~9900W	0~19800W	
	Resolution	100mW	500mW	1000mW	
	Accuracy	0.1%+0.1%F.S.			
Sampling Frequency	500kHz				
<b>Protection</b>					
OVP	153V	612V	1224V		
OCP	73.44A	367.2A	734.4A		
OPP	2019.6W	10098W	20196W		
Over Temperature	70~75°C				
Overvoltage Safety Value	110%VF.S.				
Reverse Protection	Yes				
Alarm Tone	Yes				
<b>Mechanical</b>					
Dimensions(WxHxD)	423x442x670mm				
Package Dimensions(WxHxD)	/				
Unit Net Weight	110kg				
Net Weight	/				
<b>AC Input</b>					
Voltage	100~240Vac				
Frequency	50~60Hz				
Power	700VA				
Fuse	8A				

# Programmable DC Electronic Load

MODEL		EL1200VDC22000W		
Rated	Voltage	0~1200V		
	Current	0~800A		
	Power	0~22000W		
	Min. Operating Voltage	2V@80A	10V@400A	20V@800A
<b>Static Mode</b>				
Constant Current Mode	Range	0~80A	0~400A	0~800A
	Resolution	1mA	5mA	10mA
	Accuracy	0.05%+0.05%F.S.		
Constant Voltage Mode	Range	0~150V	0~600V	0~1200V
	Resolution	1mV	5mV	10mV
	Accuracy	0.025%+0.025%F.S.		
Constant Power Mode	Range	0~2200W	0~11000W	0~22000W
	Resolution	100mW	500mW	1000mW
	Accuracy	0.2%+0.2%F.S.		
Constant Resistance Mode	Range	15mΩ~150Ω(150V)	60mΩ~600Ω(600V)	600mΩ~1200Ω(1200V)
	Resolution	15mΩ(150V)	60mΩ(600V)	600mΩ(1200V)
	Accuracy	Vin/Rset*(0.2%)+0.2% I.F.S.		
<b>Dynamic Mode</b>				
CCD/CRD	T1&T2(Pro.)	0.02ms~300s		
	T1&T2(Adv.)	0.05ms~300s		
	Resolution	1μs		
	Accuracy	1μs+100ppm		
	Slew Rate(Pro.)	1mA/μs~2.7A/μs	5mA/μs~13.3A/μs	10mA/μs~26.7A/μs
	Slew Rate(Adv.)	1mA/μs~0.8A/μs	5mA/μs~4A/μs	10mA/μs~8A/μs
	Min. Rise Time(Pro.)	20μs(Typical)		
	Min. Rise Time(Adv.)	50μs(Typical)		
	Resolution	1mA/μs	5mA/μs	10mA/μs
	Accuracy	5%±10us		
<b>Measurement</b>				
Voltage	Range	0~150V	0~600V	0~1200V
	Resolution	1mV	5mV	10mV
	Accuracy	0.015%+0.015%F.S.		
Current	Range	0~80A	0~400A	0~800A
	Resolution	1mA	5mA	10mA
	Accuracy	0.04%+0.06%F.S.		
Power	Range	0~2200W	0~11000W	0~22000W
	Resolution	100mW	500mW	1000mW
	Accuracy	0.1%+0.1%F.S.		
Sampling Frequency	500kHz			
<b>Protection</b>				
OVP	153V	612V	1224V	
OCP	81.6A	408A	816A	
OPP	2244W	11220W	22440W	
Over Temperature	70~75°C			
Overvoltage Safety Value	110%V.F.S.			
Reverse Protection	Yes			
Alarm Tone	Yes			
<b>Mechanical</b>				
Dimensions(WxHxD)	423x575x670mm			
Package Dimensions(WxHxD)	/			
Unit Net Weight	145kg			
Net Weight	/			
<b>AC Input</b>				
Voltage	100~240Vac			
Frequency	50~60Hz			
Power	900VA			
Fuse	10A			

# Programmable DC Electronic Load

MODEL		EL1200VDC24200W			
Rated	Voltage	0~1200V			
	Current	0~880A			
	Power	0~24200W			
	Min. Operating Voltage	2V@88A	10V@440A	20V@880A	
<b>Static Mode</b>					
Constant Current Mode	Range	0~88A	0~440A	0~880A	
	Resolution	1mA	5mA	10mA	
	Accuracy	0.05%+0.05%F.S.			
Constant Voltage Mode	Range	0~150V	0~600V	0~1200V	
	Resolution	1mV	5mV	10mV	
	Accuracy	0.025%+0.025%F.S.			
Constant Power Mode	Range	0~2420W	0~12100W	0~24200W	
	Resolution	100mW	500mW	1000mW	
	Accuracy	0.2%+0.2%F.S.			
Constant Resistance Mode	Range	13.6mΩ~136Ω(150V)	55mΩ~550Ω(600V)	550mΩ~1100Ω(1200V)	
	Resolution	13.6mΩ(150V)	55mΩ(600V)	550mΩ(1200V)	
	Accuracy	Vin/Rset*(0.2%)+0.2% I.F.S.			
<b>Dynamic Mode</b>					
CCD/CRD	T1&T2(Pro.)	0.02ms~300s			
	T1&T2(Adv.)	0.05ms~300s			
	Resolution	1μs			
	Accuracy	1μs+100ppm			
	Slew Rate(Pro.)	1mA/μs~2.93A/μs	5mA/μs~14.7A/μs	10mA/μs~29.3A/μs	
	Slew Rate(Adv.)	1mA/μs~0.88A/μs	5mA/μs~4.4A/μs	10mA/μs~8.8A/μs	
	Min. Rise Time(Pro.)	20μs(Typical)			
	Min. Rise Time(Adv.)	50μs(Typical)			
	Resolution	1mA/μs	5mA/μs	10mA/μs	
	Accuracy	5%±10us			
<b>Measurement</b>					
Voltage	Range	0~150V	0~600V	0~1200V	
	Resolution	1mV	5mV	10mV	
	Accuracy	0.015%+0.015%F.S.			
Current	Range	0~88A	0~440A	0~880A	
	Resolution	1mA	5mA	10mA	
	Accuracy	0.04%+0.06%F.S.			
Power	Range	0~2420W	0~12100W	0~24200W	
	Resolution	100mW	500mW	1000mW	
	Accuracy	0.1%+0.1%F.S.			
Sampling Frequency	500kHz				
<b>Protection</b>					
OVP	153V	612V	1224V		
OCP	89.76A	448.8A	897.6A		
OPP	2468.4W	12342W	24684W		
Over Temperature	70~75°C				
Overvoltage Safety Value	110%VF.S.				
Reverse Protection	Yes				
Alarm Tone	Yes				
<b>Mechanical</b>					
Dimensions(WxHxD)	423x575x670mm				
Package Dimensions(WxHxD)	/				
Unit Net Weight	145kg				
Net Weight	/				
<b>AC Input</b>					
Voltage	100~240Vac				
Frequency	50~60Hz				
Power	900VA				
Fuse	10A				

# Programmable DC Electronic Load

MODEL		EL1200VDC26400W			
Rated	Voltage	0~1200V			
	Current	0~960A			
	Power	0~26400W			
	Min. Operating Voltage	2V@96A	10V@480A	20V@960A	
<b>Static Mode</b>					
Constant Current Mode	Range	0~96A	0~480A	0~960A	
	Resolution	1mA	5mA	10mA	
	Accuracy	0.05%+0.05%F.S.			
Constant Voltage Mode	Range	0~150V	0~600V	0~1200V	
	Resolution	1mV	5mV	10mV	
	Accuracy	0.025%+0.025%F.S.			
Constant Power Mode	Range	0~2640W	0~13200W	0~26400W	
	Resolution	100mW	500mW	1000mW	
	Accuracy	0.2%+0.2%F.S.			
Constant Resistance Mode	Range	12.5mΩ~125Ω(150V)	50mΩ~500Ω(600V)	500mΩ~1000Ω(1200V)	
	Resolution	12.5mΩ(150V)	50mΩ(600V)	500mΩ(1200V)	
	Accuracy	Vin/Rset*(0.2%)+0.2% I.F.S.			
<b>Dynamic Mode</b>					
CCD/CRD	T1&T2(Pro.)	0.02ms~300s			
	T1&T2(Adv.)	0.05ms~300s			
	Resolution	1μs			
	Accuracy	1μs+100ppm			
	Slew Rate(Pro.)	1mA/μs~3.2A/μs	5mA/μs~16A/μs	10mA/μs~32A/μs	
	Slew Rate(Adv.)	1mA/μs~0.96A/μs	5mA/μs~4.8A/μs	10mA/μs~9.6A/μs	
	Min. Rise Time(Pro.)	20μs(Typical)			
	Min. Rise Time(Adv.)	50μs(Typical)			
	Resolution	1mA/μs	5mA/μs	10mA/μs	
	Accuracy	5%±10us			
<b>Measurement</b>					
Voltage	Range	0~150V	0~600V	0~1200V	
	Resolution	1mV	5mV	10mV	
	Accuracy	0.015%+0.015%F.S.			
Current	Range	0~96A	0~480A	0~960A	
	Resolution	1mA	5mA	10mA	
	Accuracy	0.04%+0.06%F.S.			
Power	Range	0~2640W	0~13200W	0~26400W	
	Resolution	100mW	500mW	1000mW	
	Accuracy	0.1%+0.1%F.S.			
Sampling Frequency	500kHz				
<b>Protection</b>					
OVP	153V	612V	1224V		
OCP	97.92A	489.6A	979.2A		
OPP	2692.8W	13464W	26928W		
Over Temperature	70~75°C				
Overvoltage Safety Value	110%V.F.S.				
Reverse Protection	Yes				
Alarm Tone	Yes				
<b>Mechanical</b>					
Dimensions(WxHxD)	423x575x670mm				
Package Dimensions(WxHxD)	/				
Unit Net Weight	145kg				
Net Weight	/				
<b>AC Input</b>					
Voltage	100~240Vac				
Frequency	50~60Hz				
Power	900VA				
Fuse	10A				

1200V Series System Specifications			
<b>Non Linear Mode</b>			
Range	CL	30uF~50000uF	
	RL	As CR Mode	
	Ls	0.1uH~16uH	
	Rs	30mΩ~20Ω	
Resolution	CL	1uF	
	RL	As CR Mode	
	Ls	0.1uH	
	Rs	1mΩ	
<b>Battery Discharge Mode</b>			
Battery Voltage	As CV Mode		
Current Resolution	As CC Mode		
Record	AH/WH		
Test Time	1s~100000s		
Time Resolution	1s		
<b>Program Mode</b>			
Step No.	300 Max.		
Dwell	0.1ms~4000s		
Spec Check	Voltage/Current/Power		
<b>External Waveform Control/Monitor</b>			
Control/Monitor	Voltage/Current		
Input/Output Range	0~10V		
Voltage Range	0~L_range F.S.	0~M_range F.S.	0~H_range F.S.
Current Range	0~L_range F.S.	0~M_range F.S.	0~H_range F.S.
Accuracy	0.4%F.S.		
Resolution	4mV		
Bandwidth	20kHz		
Input Impedance	10kΩ		
<b>Short Circuit</b>			
Current(CC)	Full range current value		
Voltage(CV)	Voltage value at the Max power in working mode		
Resistance(CR)	Min resistance value of CR Mode		
<b>Master/Slave</b>			
Parallel Interface	RJ45		
Parallel Quantity (Pro.)	20 units		
Parallel Quantity (Adv.)	10 units		
<b>General</b>			
Graphic Display	4.3"Color touch LCD		
Operation Key Feature	Soft key, Numeric key, Rotary Knob, Support USB disk		
Rack Mount Handles	Yes		
FAN	Temperature Control		
Interface	RS232/RS485/USB(Standard), GPIB/LAN(Optional)		
Communication Response Time	30ms		
Storage Capacity	User defined settings (300 sets), OCP settings (10 sets), OPP settings (10 sets), Default settings (1 set), Factory setting (1 set)		
<b>Environmental</b>			
Operating Temperature	0~40°C		
Storage Temperature	-20~80°C		
Temperature Coefficient	100ppm/°C(Typical)		
Relative Humidity	10~90%RH		
Altitude	≤2000m		
<b>Regulatory Compliance</b>			
Overvoltage Category	II		
Protection Degree	I		
Pollution Degree	II		
Input Impedance	2MΩ(Typical)		
Isolation Voltage	/		
Certificates	CE		


All specifications are subject to change without notice.

# Programmable DC Electronic Load

---

## PS :

1. Each model size indicated here does not include the wheel and the protective cover.
2. Minimum rise time is valid only for loading current > 5%F.S.
3. The measured noise is 79dB which is tested under the condition of 40 °C ambient temperature with full power for 5 minutes and 1 meter away from the rear panel.
4. If the operating voltage exceeds the rated voltage for 1.1 times, it will cause permanent damage to the unit.
5. The over temperature protection sampling point is located in the vent.
6. The power rating specifications of 1200V models as below.



7. All the specifications are tested at temperature of 25°C, unless otherwise noted.

APM Technologies (Dongguan) Co., Ltd

Add: #7, Link Information Industry Park, Shuilianshan Road,  
Nancheng, Dongguan, Guangdong, China

Tel: +86 769-2202 8588 ext:2892 Fax: +86 769-2202 6771

E-mail: [overseas@apmtech.cn](mailto:overseas@apmtech.cn) Web: [en.apmtech.cn](http://en.apmtech.cn)